


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 NE 1/4 SW 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W	
Distance and direction from nearest town or city street address of well if located within city? 849 Crescent Lakes Ct. Andover, Kansas						
2	WATER WELL OWNER: H & H Home Builders Inc.	RR#, ST. ADDRESS, BOX #: 3865 N. Lakecrest Ct.	Board of Agriculture, Division of Water Resource			
	CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Number:			
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL Est. Yield: Bore Hole Diameter	97 ft.	ELEVATION: ft. below land surface measured on mo/day/yr:	8/21/07	
		Pump test data: Well water was Well water was	ft. after	hours of pumping @ gpm		
		ft. after	hours of pumping @ gpm			
		12 in. to 97 ft.	and in. to ft.			
		WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 2. Irrigation 4. Industrial 6. Oil field water supply Was a chemical/bacteriological sample submitted to Department?	9. Dewatering 11. Injection well 12. Other (Specify below)			
		7. Lawn and garden only	YES NO			
		8. Air conditioning	10. Monitoring well			
		Was Water Well Disinfectated?	12. Other (Specify below)			
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC	5. Wrought Iron 4. ABS	7. Fiberglass 6. Asbestos-Cement 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Welded	Threaded Clamped
	Blank casing diameter 5 in.	to 37 ft.	Dia.	in. to ft.	ft. Dia.	in. to ft.
	Casing height above land surface: 12 in.	Weight: 2.35 lbs. / ft.			Wall thickness or gauge No.	.214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)						7. PVC
	9. ABS 10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped						7. Torch cut 8. Saw cut
	9. Drilled holes 10. Other (specify)	11. None (open hole)				
SCREEN - PERFORATION INTERVAL From 37 ft. to 97 ft., From ft. to ft.						From ft. to ft.
GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.						From ft. to ft.
6	GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From ft. to ft.	1. Neat cement 2. Cement Grout 3. Bentonite	Other	bentonite hole plug		
	What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well		
	South	How many feet? 50 ft. plus				
	From To	LITHOLOGIC LOG		From To	LITHOLOGIC LOG	
0	4	topsoil				
4	20	clay				
20	97	shale				
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 8/21/2007 and this record is true to the best of my knowledge and belief.					
	Kansas Water Well Contractor's License No. 236			This water well record was completed on (mo/day/year) 8/24/2007		
	under the business name of Harp Well and Pump Service			by (signature) Todd S. Harp		