


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 SW 1/4 SE 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city? 1102 Rosemont Place (1/2 E. of Andover Rd., 300' N. of Central) Andover, Kansas							
2 WATER WELL OWNER: H & H Home Builders Inc. RR#, ST. ADDRESS, BOX #: 3865 N. Lakecrest Ct. CITY, STATE: Wichita, Kansas	Board of Agriculture, Division of Water Resource						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 100 ft.	ELEVATION: ft.	ft.				
Depth of groundwater Encountered: ft. ft. ft.							
WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/20/07							
Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm							
Bore Hole Diameter 12 in. to 100 ft. and in. to ft.							
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)							
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO							
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Threaded Welded Clamped			
Blank casing diameter 5 in. to 40 ft., Dia.	in. to ft.	ft., Dia.	in. to ft.				
Casing height above land surface: 12 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)							
SCREEN - PERFORATION INTERVAL From 40 ft. to 100 ft., From ft. to ft. From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 24 ft. to 100 ft., From ft. to ft., From ft. to ft.							
6 GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.	1. Neat cement 2. Cement Grout 3. Bentonite	Other bentonite hole plug					
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage							
Direction from well?: East	How many feet? 20 ft. plus						
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	3	topsoil					
3	11	clay					
11	60	brown shale					
60	100	grey shale					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/20/2007 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236			This water well record was completed on (mo/day/year) 9/24/2007				
under the business name of Harp Well and Pump Service			by (signature) Todd S. Harp				