


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 SE 1/4 SE 1/4	SECTION NUMBER 7	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city? 1/4 mile West of Andover Rd, North side of 13th St. N. Andover, Kansas							
2 WATER WELL OWNER: COOPER, Chuck	RR#, ST. ADDRESS, BOX #: 1336 N. Robin Ct.	Board of Agriculture, Division of Water Resource					
CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 115 ft.	ELEVATION:					
Depth of groundwater Encountered:	ft.	ft.	ft.				
WELL'S STATIC WATER LEVEL Pump test data: Est. Yield: gpm	40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/23/08	Well water was	ft. after	hours of pumping @ gpm			
Bore Hole Diameter 12 in.	to 115 ft.	Well water was	ft. after	hours of pumping @ gpm			
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning Was a chemical/bacteriological sample submitted to Department?	9. Dewatering 10. Monitoring well	11. Injection well 12. Other (Specify below)					
Was Water Well Disinfected?	YES	NO	; If yes, what mo/day/yr was sample				
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Threaded Clamped	Blank casing diameter 5 in. to 25 ft., Dia. in. to ft., Dia. in. to ft.						
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214						
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)							
SCREEN - PERFORATION INTERVAL From 25 ft. to 115 ft., From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 24 ft. to 115 ft., From ft. to ft., From ft. to ft.							
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug							
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage							
Direction from well?: West	How many feet? 20 ft. plus						
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	3	topsoil					
3	10	clay					
10	115	gray shale					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 5-23-2008 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 5-28-2008						
under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp						