


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NW NW SW SE SE 1/4 NW 1/4 SE 1/4	SECTION NUMBER 356	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3 E E/W
Distance and direction from nearest town or city street address of well if located within city? 2243 S. Silver Dale Wichita, Kansas				
2 WATER WELL OWNER: RR#, ST. ADDRESS, BOX #: CITY, STATE:	MC CLELLAN ENTERPRISE 1108 W. 34th St. N. Wichita, Kansas	Board of Agriculture, Division of Water Resource ZIP CODE: 67204 Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION: Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 45 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/7/08 Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 110 ft. and in. to ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES 12. Other (Specify below) Was Water Well Disinfected? YES ; If yes, what mo/day/yr was sample NO			
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC (circled) 4. ABS	5. Wrought Iron 7. Fiberglass 9. Other (Specify below) 6. Asbestos-Cement 8. Concrete tile SDR-26	CASING JOINTS: Glued Threaded Welded Clamped		
Blank casing diameter 5 in. to 50 ft., Dia. in. to ft., Dia. in. to ft.	Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214			
Casing height above land surface: 12 in.,				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)				
SCREEN - PERFORATION INTERVAL From 50 ft. to 110 ft., From ft. to ft. From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 24 ft. to 110 ft., From ft. to ft., From ft. to ft.				
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line (circled) 6. Seepage pit 9. Feed yard 12. Fertilizer storage				
Direction from well? South How many feet? 10 ft. plus				
From To LITHOLOGIC LOG From To LITHOLOGIC LOG				
0 4	topsoil			
4 15	clay			
15 110	shale			
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 7/7/2008 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 236			This water well record was completed on (mo/day/year) 7/11/2008	
under the business name of Harp Well and Pump Service			by (signature) Todd S. Harp	