

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL:

County: Bartley

Fraction

SE 1/4 NW 1/4 NE 1/4

Section Number

29

Township Number

T 27 S

Range Number

R 3 E WDistance and direction from nearest town or city street address of well if located within city? 2 Mile S of Andover Kan

Global Positioning Systems (decimal degrees, min. of 4 digits)

Latitude: _____

Longitude: _____

Elevation: _____

Datum: _____

Data Collection Method: _____

2 WATER WELL OWNER:


RR#, St. Address, Box #

City, State, ZIP Code

Greg Pate 67133
Andover Kan Park
2571 E. Flint Hills Way

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N



S

4 DEPTH OF COMPLETED WELL ft.

Depth(s) Groundwater Encountered (1) 80 ft. (2) ft. (3) ft.WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr.

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 35 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring wellWas a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrSample was submitted Water well disinfected? Yes X No

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR)

2 PVC 4 ABS

5 Wrought Iron

6 Asbestos-Cement

7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued X Clamped

Welded

Threaded

Blank casing diameter 5 in. to 30 ft., Diameter 18 in. to 160 lbs./ft. Wall thickness or guage No. 1214Casing height above land surface 18 in., Weight 160 lbs./ft. Wall thickness or guage No. 1214

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel 5 Fiberglass

2 Brass 4 Galvanized Steel 6 Concrete tile

7 PVC

9 ABS

11 Other (Specify)

8 RM (SR)

10 Asbestos-Cement

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)SCREEN-PERFORATED INTERVALS: From 30 ft. to 125 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 30 ft. to 125 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 OtherGrout Intervals: From 3 ft. to 23 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

13 Insecticide Storage

16 Other (specify

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

14 Abandoned water well

below)

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer Storage

15 Oil well/gas well

Direction from well? WHow many feet? 80

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>5</u>	<u>Soil</u>			
<u>5</u>	<u>15</u>	<u>Clay</u>			
<u>15</u>	<u>20</u>	<u>Rock</u>			
<u>20</u>	<u>125</u>	<u>Shale + Lime</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/19/08 and this record is true to the best of my knowledge and belief.Kansas Water Well Contractor's License No. 257 This Water Well Record was completed on (mo/day/year) 8/19/08 under the business name of Winter Well Drill by (signature) Charles WinterINSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.