


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NE 1/4 SE 1/4 NW 1/4	SECTION NUMBER 8	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city? 843 Crescent Lakes Place Andover, Kansas							
2 WATER WELL OWNER: RR#, ST. ADDRESS, BOX #: CITY, STATE:	PETERS, Matt 843 Crescent Lakes Place Andover, Kansas		Board of Agriculture, Division of Water Resource Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 103 ft.	ELEVATION: ft. ft. ft.					
Depth of groundwater Encountered: ft. ft. ft.							
WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 8/18/08							
Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm							
Bore Hole Diameter 12 in. to 103 ft. and in. to ft.							
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)							
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO							
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Threaded Welded Clamped			
Blank casing diameter 5 in. to 43 ft., Dia.	in. to	ft., Dia.	in. to	ft.			
Casing height above land surface: 12 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)							
SCREEN - PERFORATION INTERVAL From 43 ft. to 103 ft., From ft. to ft. From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 24 ft. to 103 ft., From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6 GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft., From ft. to ft.	1. Neat cement 2. Cement Grout 3. Bentonite	Other bentonite hole plug					
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)			
Direction from well? West	How many feet? 10 ft. plus						
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	3	fill dirt					
3	15	clay					
15	85	shale					
85	103	limestone & shale					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 8/18/2008 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 8/22/2008						
under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp						