


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 SE 1/4 SW 1/4	SECTION NUMBER 30	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 1515 Haney So. Ct. (54 & 159th E., South and East Andover, Kansas)				
2 WATER WELL OWNER: ANAYA, Mark RR#, ST. ADDRESS, BOX #: 1515 Haney So. Ct. CITY, STATE: Andover, Kansas	Board of Agriculture, Division of Water Resource			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 80 ft.	ELEVATION: ft.	ft.	
Depth of groundwater Encountered: ft. ft.				
WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/8/08				
Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm				
Bore Hole Diameter 12 in. to 80 ft. and in. to ft.				
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. <u>Lawn and garden only</u> 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES 12. Other (Specify below) Submitted NO ; If yes, what mo/day/yr was sample				
Was Water Well Disinfected? YES 13. <u>YES</u> NO				
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: <u>Glued</u> Threaded Welded Clamped
Blank casing diameter 5 in. to 30 ft., Dia.	in. to	ft., Dia.	in. to	ft., Dia. in. to ft.
Casing height above land surface: 12 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214		
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)				
SCREEN - PERFORATION INTERVAL From 30 ft. to 80 ft., From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 24 ft. to 80 ft., From ft. to ft., From ft. to ft.				
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? West How many feet? 10 ft. plus				
7 Contractor's or Landowner's Certification: This water well was 1. <u>constructed</u> 2. <u>reconstructed</u> or 3. <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 9/8/2008 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/10/2008 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp				