


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL: Butler	FRACTION SE 1/4 NW 1/4 NW 1/4	SECTION NUMBER 7	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W	
Distance and direction from nearest town or city street address of well if located within city? 2025 Roger Ct. Andover, Kansas						
2	WATER WELL OWNER: MILLER, David	RR#, ST. ADDRESS, BOX #: 2025 Roger Ct.	Board of Agriculture, Division of Water Resource			
	CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:			
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 110 ft.	ELEVATION:			
	Depth of groundwater Encountered:	ft.	ft.	ft.		
	WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr:	11/4/08			gpm	
	Pump test data: Well water was	ft. after	hours of pumping @	gpm		
	Est. Yield: gpm	Well water was	ft. after	hours of pumping @	gpm	
	Bore Hole Diameter 12 in.	to 110 ft.	and	in.	to ft.	
	WELL WATER TO BE USED AS:	9. Dewatering 11. Injection well				
	1. Domestic 3. Feedlot 5. Public water supply	12. Other (Specify below)				
	2. Irrigation 4. Industrial 6. Oil field water supply	7. Lawn and garden only	8. Air conditioning	10. Monitoring well		
	Was a chemical/bacteriological sample submitted to Department? YES	NO	Was Water Well Disinfected? YES	NO		
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below)	CASING JOINTS: Glued Welded	Threaded Clamped
	Blank casing diameter 5 in.	to 40 ft.,	Dia.	in. to	ft., Dia.	in. to ft.
	Casing height above land surface: 12 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214			
	TYPE OF SCREEN OR PERFORATION MATERIAL:					
	1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC	9. ABS 8. RMP (SR)	10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)	
	SCREEN OR PERFORATION OPENINGS ARE:					
	1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped	7. Torch cut 8. Saw cut	9. Drilled holes 10. Other (specify)	11. None (open hole)		
	SCREEN - PERFORATION INTERVAL From 40 ft. to 110 ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.
	GRAVEL PACK INTERVALS: From 24 ft. to 110 ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.
6	GROUT MATERIALS: 1. Neat cement Grout Intervals: From 4 ft. to 24 ft.,	2. Cement Grout From ft. to ft.,	3. Bentonite ft. to ft.,	Other	bentonite hole plug	
	What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)	
	Direction from well?: North	How many feet? 10 ft. plus				
	From 0 To 4 topsoil	LITHOLOGIC LOG		From 4 To 15	LITHOLOGIC LOG	
	4 To 15 clay			15 To 110 shale		
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 11/04/2008 and this record is true to the best of my knowledge and belief.					
	Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 11-7-2008				
	under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp				