


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 NW 1/4 SE 1/4	SECTION NUMBER 5	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W	
Distance and direction from nearest town or city street address of well if located within city? 3/8 mile North of 21st St. North, 1/2 mile West of Andover Road Andover, Kansas					
2 WATER WELL OWNER: WAMPLER, Mike	RR#, ST. ADDRESS, BOX #: 2449 N. Sandstone	Board of Agriculture, Division of Water Resource			
CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 97 ft.	ELEVATION: ft.	ft.		
	Depth of groundwater Encountered: ft.		ft.		
	WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON (mo/day/yr): 7/28/09				
	Pump test data: Est. Yield: gpm	Well water was ft. after	hours of pumping @ ft. after	gpm	
	Bore Hole Diameter 12 in.	Well water was ft. and	hours of pumping @ in. to ft.	gpm	
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only	9. Dewatering	11. Injection well		
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning	10. Monitoring well	12. Other (Specify below)		
	Was a chemical/bacteriological sample submitted to Department? submitted	YES NO	Was Water Well Disinfected? YES	NO	
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) Casing joints: SDR-26	Glued Threaded Welded Clamped
	Blank casing diameter 5 in.	to 47 ft.	Dia. in.	to ft.	Dia. in. to ft.
	Casing height above land surface: 12 in.	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214		
	TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	9. ABS 10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)		
	SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)				
	SCREEN - PERFORATION INTERVAL From 47 ft. to 97 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	
	GRAVEL PACK INTERVALS: From 24 ft. to 97 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	
6	GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft.	2. Cement Grout	3. Bentonite	Other	bentonite hole plug
	What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage				
	Direction from well? West	How many feet? 10 ft. plus			
	From 0 To 4 topsoil	LITHOLOGIC LOG		From 4 To 30	LITHOLOGIC LOG
	From 4 To 30 clay			From 30 To 97 shale	
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 7/28/2009 and this record is true to the best of my knowledge and belief.				
	Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year)		7/31/2009	
	under the business name of Harp Well and Pump Service	by (signature)		Todd S. Harp	