


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL: Butler	FRACTION SE 1/4 NE 1/4 SW 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 1113 Woodstone Dr. Andover, Kansas					
2	WATER WELL OWNER: GEARHART, JIM HOMES	RR#, ST. ADDRESS, BOX #: 1111 Coach House Ct.	Board of Agriculture, Division of Water Resource		
	CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Number:		
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4	DEPTH OF COMPLETED WELL: 75 ft.	ELEVATION: ft.	ft.
			Depth of groundwater Encountered: ft.		
			WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/5/10		
			Pump test data: Well water was ft. after hours of pumping @ gpm		
			Est. Yield: gpm Well water was ft. after hours of pumping @ gpm		
			Bore Hole Diameter 12 in. to 75 ft. and in. to ft.		
			WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES NO 12. Other (Specify below)		
			Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO		
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Threaded Welded Clamped
	Blank casing diameter 5 in. to 25 ft., Dia.	in. to	ft., Dia.	in. to	ft.
	Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft.			Wall thickness or gauge No. .214	
	TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC 8. RMP (SR)	9. ABS 10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)	
	SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped	7. Torch cut 8. Saw cut	9. Drilled holes 10. Other (specify)	11. None (open hole)	
	SCREEN - PERFORATION INTERVAL From 25 ft. to 75 ft., From ft. to ft., From ft. to ft.				
	GRAVEL PACK INTERVALS: From 25 ft. to 75 ft., From ft. to ft., From ft. to ft.				
6	GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.	1. Neat cement 4. Lateral lines 5. Cess Pool 6. Seepage pit	2. Cement Grout 7. Pit privy 8. Sewage lagoon 9. Feed yard	3. Bentonite 10. Livestock pens 11. Fuel storage 12. Fertilizer storage	Other bentonite hole plug 13. Insecticide storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below)
	What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line				Direction from well? North How many feet? 10 ft. plus
	From To	LITHOLOGIC LOG		From To	LITHOLOGIC LOG
0	3	topsoil			
3	7	clay			
7	75	gray shale			
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10/5/2010 and this record is true to the best of my knowledge and belief.				
	Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10/8/2010				
	under the business name of Harp Well and Pump Service			by (signature) Todd S. Harp	