


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL: Butler	FRACTION SE 1/4 NE 1/4 SW 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 1109 Woodstone Dr. Andover, Kansas					
2	WATER WELL OWNER: H & H HOMEBUILDERS INC. RR#, ST. ADDRESS, BOX #: 3865 N. Lakecrest Ct. CITY, STATE: Wichita, Kansas	Board of Agriculture, Division of Water Resource			
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 85 ft.	ELEVATION: ft. ft. ft.		
1 Mile	Depth of groundwater Encountered: ft.	WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/5/10			
	Pump test data: Est. Yield: gpm	Well water was Well water was	ft. after ft. after	hours of pumping @ hours of pumping @	gpm gpm
	Bore Hole Diameter 12 in.	to 85 ft.	and	in. to	ft.
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 2. Irrigation 4. Industrial 6. Oil field water supply	7. Lawn and garden only	9. Dewatering 10. Monitoring well	11. Injection well 12. Other (Specify below)	
	Was a chemical/bacteriological sample submitted to Department? submitted	YES NO	; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO		
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile	9. Other (Specify below)	CASING JOINTS: Glued Welded	Threaded Clamped	
	Blank casing diameter 5 in. to 30 ft., Dia.	in. to	ft., Dia.	in. to ft.	
	Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214			
	TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC 8. RMP (SR)	9. ABS 10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)	
	SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)				
	SCREEN - PERFORATION INTERVAL From 30 ft. to 85 ft., From ft. to ft., From ft. to ft.				
	GRAVEL PACK INTERVALS: From 24 ft. to 85 ft., From ft. to ft., From ft. to ft.				
6	GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.	Other	bentonite hole plug		
	What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)		
	Direction from well? North	How many feet? 10 ft. plus			
	LITHOLOGIC LOG		LITHOLOGIC LOG		
From	To		From	To	
0	3	topsoil			
3	7	clay			
7	85	gray shale			
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10/5/2010 and this record is true to the best of my knowledge and belief.				
	Kansas Water Well Contractor's License No. 236		This water well record was completed on (mo/day/year) 10/8/2010		
	under the business name of Harp Well and Pump Service		by (signature) Todd S. Harp		