


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NE 1/4 SE 1/4 NW 1/4	SECTION NUMBER 7	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E EW			
Distance and direction from nearest town or city street address of well if located within city? 1916 N. Remington Ct. Andover, Kansas							
2 WATER WELL OWNER: HUMPHRIES, Mark	RR#, ST. ADDRESS, BOX #: 1916 N. Remington Ct.	Board of Agriculture, Division of Water Resource					
CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 116 ft.	ELEVATION:					
Depth of groundwater Encountered:	ft.	ft.	ft.				
WELL'S STATIC WATER LEVEL Bore Hole Diameter WELL WATER TO BE USED AS:	30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 6/16/11	Pump test data: Est. Yield: gpm	Well water was ft. after	hours of pumping @ gpm			
			Well water was ft. after	hours of pumping @ gpm			
		Bore Hole Diameter 12 in.	to 116 ft.	and in. to ft.			
		1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only	9. Dewatering 11. Injection well	12. Other (Specify below)			
		2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning	10. Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? YES NO	; If yes, what mo/day/yr was sample submitted				
		Was Water Well Disinfected? YES	NO				
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 7. Fiberglass	9. Other (Specify below)	CASING JOINTS: Glued	Threaded			
	6. Asbestos-Cement 8. Concrete tile	SDR-26	Welded	Clamped			
Blank casing diameter 5 in.	to 30 ft., Dia.	in. to ft., Dia.	in. to ft.				
Casing height above land surface: 12 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC 8. RMP (SR)	9. ABS 10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped	7. Torch cut 8. Saw cut	9. Drilled holes 10. Other (specify)	11. None (open hole)				
SCREEN - PERFORATION INTERVAL From 30 ft. to 116 ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.			
GRAVEL PACK INTERVALS: From 24 ft. to 116 ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.			
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite	Other bentonite hole plug						
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.			
What is the nearest source of possible contamination:							
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)					
Direction from well? East How many feet? 10 ft. plus							
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	3	topsoil					
3	12	clay					
12	30	brown shale					
30	116	gray shale					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 6/16/2011 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236					This water well record was completed on (mo/day/year) 6/20/2011		
under the business name of Harp Well and Pump Service					by (signature) Todd S. Harp		