


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NE 1/4 NW 1/4 NW 1/4	SECTION NUMBER 8	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city 21st N. and Andover Rd. Andover, Kansas				
2 WATER WELL OWNER: ANDOVER LANDING	RR#, ST. ADDRESS, BOX #: 150 N. Market	Board of Agriculture, Division of Water Resource		
CITY, STATE: Wichita, Kansas		ZIP CODE:	Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 116 ft.	ELEVATION: ft.	ft.	
Depth of groundwater Encountered: ft. ft.				
WELL'S STATIC WATER LEVEL 50 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 6/27/11				
Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 116 ft. and in. to ft.				
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. <u>Lawn and garden only</u> 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES <u>NO</u> ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO				
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: <u>Glued</u> Threaded Welded Clamped
Blank casing diameter 5 in.	to 30 ft.	Dia.	in. to ft.	Dia. in. to ft.
Casing height above land surface: 12 in.	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214		
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. <u>PVC</u> 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. <u>Saw cut</u> 10. Other (specify)				
SCREEN - PERFORATION INTERVAL From 30 ft. to 116 ft., From ft. to ft. From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 24 ft. to 116 ft., From ft. to ft., From ft. to ft.				
6 GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.	1. Neat cement 2. Cement Grout 3. Bentonite	Other	bentonite hole plug	
What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line	4. Lateral lines 5. Cess Pool 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well 15. Oil well/Gas well 16. Other (specify below) None Apparent
Direction from well? How many feet?				
From	To	LITHOLOGIC LOG		From To LITHOLOGIC LOG
0	3	topsoil		
3	10	clay		
10	20	brown shale		
20	116	gray shale		
7 Contractor's or Landowner's Certification: This water well was 1. <u>constructed</u> 2. <u>reconstructed</u> or 3. <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 6/27/2011 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 236		This water well record was completed on (mo/day/year) 6/30/2011		
under the business name of Harp Well and Pump Service		by (signature) Todd S. Harp		