


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 NW 1/4 SE 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W		
Distance and direction from nearest town or city street address of well if located within city? 801 Fairoaks Ct. Andover, Kansas							
2	WATER WELL OWNER: NIES CONSTRUCTION	RR#, ST. ADDRESS, BOX #: 10333 E. 21st #303	Board of Agriculture, Division of Water Resource				
	CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Number:				
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 86	ft.	ELEVATION:	ft.		
	Depth of groundwater Encountered:	ft.	ft.		ft.		
	WELL'S STATIC WATER LEVEL 20	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr:	6/22/11			
	Pump test data: Est. Yield: gpm	Well water was	ft. after	hours of pumping @	gpm		
	Bore Hole Diameter 12 in.	Well water was	ft. after	hours of pumping @	gpm		
	WELL WATER TO BE USED AS: 1. Domestic 2. Irrigation 3. Feedlot 4. Industrial 5. Public water supply 6. Oil field water supply	9. Dewatering	11. Injection well				
	Was a chemical/bacteriological sample submitted to Department? submitted	12. Other (Specify below)					
	YES	NO					
	Was Water Well Disinfected? YES	NO					
5	TYPE OF CASING USED: 1. Steel 2. PVC 3. RPM (SR) 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below)	CASING JOINTS: Glued	Threaded	
				SDR-26	Welded	Clamped	
	Blank casing diameter 5 in.	to 25 ft.	Dia.	in. to ft.	Dia.	in. to ft.	
	Casing height above land surface: 12 in.	Weight: 2.35 lbs. / ft.			Wall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 2. Brass 3. Stainless Steel 4. Galvanized 5. Fiberglass 6. Concrete Tile 7. PVC 8. RMP (SR)						11. Other (specify)	
	10. Asbestos-Cement	12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 2. Louvered shutter 3. Mill slot 4. Key punched 5. Gauzed wrapped 6. Wire wrapped						9. Drilled holes 10. Other (specify)	11. None (open hole)
	7. Torch cut 8. Saw cut						
SCREEN - PERFORATION INTERVAL		From 25 ft.	to 86 ft.	From	ft.	to	ft.
GRAVEL PACK INTERVALS:		From 24 ft.	to 86 ft.	From	ft.	to	ft.
6	From	ft.	to	ft.	From	ft.	to
	GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite	4. Lateral lines 5. Cess Pool 6. Seepage pit	7. Pit privy 8. Sewage lagoon	9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)
	Other	bentonite hole plug					
	Grout Intervals: From 4 ft. to 24 ft.	From	ft.	to	ft.	From	ft.
	What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line 4. Lateral lines 5. Cess Pool 6. Seepage pit	7. Pit privy 8. Sewage lagoon	9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)	
	Direction from well? North	How many feet? 10 ft. plus					
	From 0 To 3 topsoil	LITHOLOGIC LOG		From 0 To 3	LITHOLOGIC LOG		
	3 8 clay						
	8 20 brown shale						
	20 86 gray shale						
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 6/22/2011 and this record is true to the best of my knowledge and belief.						
	Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 6/24/2011					
	under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp					