


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 NW 1/4 SE 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 822 Fair Oaks Ct. Andover, Kansas				
2 WATER WELL OWNER: H&H HOMEBUILDERS INC.	RR#, ST. ADDRESS, BOX #: 3906 N. Lakecrest	Board of Agriculture, Division of Water Resource		
CITY, STATE: Wichita, Kansas		ZIP CODE:	Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 100	ft.	ELEVATION:	
	Depth of groundwater Encountered:	ft.	ft.	ft.
	WELL'S STATIC WATER LEVEL Pump test data: Est. Yield: gpm	45	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr: 10/13/12
	Bore Hole Diameter WELL WATER TO BE USED AS:	12 in.	ft. after ft. after	hours of pumping @ hours of pumping @
	1. Domestic 3. Feedlot 5. Public water supply 2. Irrigation 4. Industrial 6. Oil field water supply	100	ft. and in. to	gpm gpm
	Was a chemical/bacteriological sample submitted to Department? submitted	YES	9. Dewatering Was Water Well Disinfected? NO	11. Injection well ; If yes, what mo/day/yr was sample YES NO
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile	9. Other (Specify below)	CASING JOINTS: SDR-26	Glued Welded	Threaded Clamped
Blank casing diameter 5 in. to 45 ft., Dia.	in. to	ft., Dia.	in. to	ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft.				Wall thickness or gauge No. .214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile 7. PVC 8. RMP (SR)				
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)				
SCREEN - PERFORATION INTERVAL From 45 ft. to 100 ft., From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 24 ft. to 100 ft., From ft. to ft., From ft. to ft.				
6 GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.	1. Neat cement 2. Cement Grout 3. Bentonite Other	4. Lateral lines 5. Cess Pool 6. Seepage pit 7. Pit privy 8. Sewage lagoon 9. Feed yard 10. Livestock pens 11. Fuel storage 12. Fertilizer storage 13. Insecticide storage 14. Abandon water well 15. Oil well/Gas well 16. Other (specify below)	bentonite hole plug	
What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line	West	How many feet? 10 ft. plus		
Direction from well?				
From 0 To 3 topsoil		LITHOLOGIC LOG		
From 3 To 8 clay				
From 8 To 95 gray shale				
From 95 To 100 limestone				
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10/13/2012 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 236		This water well record was completed on (mo/day/year) 10/15/2012		
under the business name of Harp Well and Pump Service		by (signature) Todd S. Harp		