


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 NW 1/4 SE 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 1102 Woodstone Andover, Kansas					
2	WATER WELL OWNER: H & H HOMEBUILDERS, INC.	RR#, ST. ADDRESS, BOX #: 3906 N. Lakecrest	Board of Agriculture, Division of Water Resource		
	CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Number:		
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 85	ft.	ELEVATION:	ft.
	Depth of groundwater Encountered:	ft.		ft.	ft.
	WELL'S STATIC WATER LEVEL 30	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr.	3/15/13	
	Pump test data: Est. Yield: 12 gpm	Well water was	ft. after	hours of pumping @	gpm
	Bore Hole Diameter 12 in.	Well water was	ft. after	hours of pumping @	gpm
	WELL WATER TO BE USED AS: 1. Domestic 2. Irrigation 3. Feedlot 4. Industrial 5. Public water supply 6. Oil field water supply	8. Air conditioning	9. Dewatering	10. Monitoring well	11. Injection well
	Was a chemical/bacteriological sample submitted to Department? submitted	YES	NO	12. Other (Specify below)	
		Was Water Well Disinfected?	YES	NO	
5	TYPE OF CASING USED: 1. Steel 2. PVC 3. RPM (SR) 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below)	CASING JOINTS: SDR-26
	Blank casing diameter 5 in.	to 30 ft.	Dia.	in. to ft.	Glued Welded
	Casing height above land surface: 12 in.		Weight: 2.35 lbs. / ft.		Threaded Clamped
	Wall thickness or gauge No. .214				
	TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 2. Brass 3. Stainless Steel 4. Galvanized 5. Fiberglass 6. Concrete Tile 7. PVC 8. RMP (SR)	9. ABS	10. Asbestos-Cement	11. Other (specify)	12. None used (open hole)
	SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 2. Louvered shutter 3. Mill slot 4. Key punched 5. Gauzed wrapped 6. Wire wrapped	7. Torch cut 8. Saw cut	9. Drilled holes 10. Other (specify)	11. None (open hole)	
	SCREEN - PERFORATION INTERVAL From 30 ft. to 85 ft.	From 24 ft. to 85 ft.	From ft. to ft.	From ft. to ft.	ft. to ft.
	GRAVEL PACK INTERVALS: From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	ft. to ft.
6	GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft.	1. Neat cement 2. Cement Grout	3. Bentonite	Other	bentonite hole plug
	What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line 4. Lateral lines 5. Cess Pool 6. Seepage pit 7. Pit privy 8. Sewage lagoon 9. Feed yard 10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)		
	Direction from well?: South	How many feet? 10 ft. plus			
	From 0 To 3 topsoil	LITHOLOGIC LOG		From 0 To 3	LITHOLOGIC LOG
	From 3 To 6 clay			From 3 To 6	
	From 6 To 20 brown shale			From 6 To 20	
	From 20 To 86 gray shale			From 20 To 86	
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 3/15/2013 and this record is true to the best of my knowledge and belief.				
	Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 3/18/2013			
	under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp			