


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 NW 1/4 SE 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W		
Distance and direction from nearest town or city street address of well if located within city? 714 Waterview Andover, Kansas						
2 WATER WELL OWNER: GEAR HART HOMES	RR#, ST. ADDRESS, BOX #: 1111 N. Coachouse Ct.	Board of Agriculture, Division of Water Resource				
CITY, STATE: Wichita, Kansas	ZIP CODE: 	Application Number: 				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 80 ft.	ELEVATION: ft.				
1 Mile	Depth of groundwater Encountered: 25 ft.	ft. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/21/13				
	WELL'S STATIC WATER LEVEL Pump test data: Est. Yield: gpm	Well water was Well water was	ft. after ft. after	hours of pumping @ hours of pumping @ gpm gpm		
	Bore Hole Diameter 12 in.	to 80 ft.	and	in. to ft.		
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 2. Irrigation 4. Industrial 6. Oil field water supply	7. <u>Lawn and garden only</u>	9. Dewatering 10. Monitoring well	11. <u>Injection well</u> 12. Other (Specify below)		
	Was a chemical/bacteriological sample submitted to Department? Was Water Well Disinfected?	YES NO	; If yes, what mo/day/yr was sample submitted YES NO			
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Welded	Threaded Clamped
	Blank casing diameter 5 in.	to 30 ft.	Dia.	in. to ft.	Dia.	in. to ft.
	Casing height above land surface: 12 in.	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214			
	TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC	9. ABS 8. RMP (SR)	10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)	
	SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped	7. Torch cut 8. Saw cut	9. Drilled holes 10. Other (specify)	11. None (open hole)		
	SCREEN - PERFORATION INTERVAL From 30 ft. to 80 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
	GRAVEL PACK INTERVALS: From 24 ft. to 80 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
6	GROUT MATERIALS: 1. Neat cement Grout Intervals: From 4 ft. to 24 ft.	2. Cement Grout From ft. to ft.	3. Bentonite From ft. to ft.	Other	bentonite hole plug	
	What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)	
	Direction from well?: North	How many feet? 10 ft. plus				
	From 0 To 3 topsoil	LITHOLOGIC LOG		From 0 To 3	LITHOLOGIC LOG	
	3 To 8 clay			8 To 25 brown shale		
	8 To 25 brown shale			25 To 80 gray shale		
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10-21-2013 and this record is true to the best of my knowledge and belief.					
	Kansas Water Well Contractor's License No. 236			This water well record was completed on (mo/day/year) 10-23-2013		
	under the business name of Harp Well and Pump Service			by (signature) Todd S. Harp		