	WATER WE	LL RECORD	Form WW	/C-5 KS	SA 82a-1212	2			
1 LOCATION OF WATER WELL:	FRACTION		SECT	ION NUMBER	TOWNSHIP	NUMBER	RANGE NU	MBER	
Butler	NE 1/4	NW 1/4 NW	V 1/4	19	T 27	s	R 3E	E/W	
Distance and direction from nearest tow	•	•							
2 WATER WELL OWNER:	ZINK, Ryan	Andover, Kansas)						
RR#,ST. ADDRESS,BOX #: 1406 W. Chaumont Circle							ulture, Division of Wa	ater Resource	
CITY, STATE:	Andover, Kansas		ZII	CODE:		Application Numl	ber:		
3 LOCATE WELL'S LOCATION	4 DEPTH OF COMPL	ETED WELL:	114 ft.		ELEVATION:				
WITH AN "X" IN SECTION BOX:	Depth of groundwater	Encountered:	ft.			ft.		ft.	
	WELL'S STATIC WAT	TER LEVEL 34	FT. BELO	W LAND SU	RFACE MEASUF	RED ON mo/da	ay/yr: 3/2 7 /	14	
NWNE	i i	np test data: Well v	vater was		ft. after	hours	of pumping @	gpm	
W Wile	Est. Yield:	31	water was	44	ft. after		of pumping @	gpm	
∑ W	E Bore Hole Diameter WELL WATER TO BE	12 in.	to 1	14 ft.	and	in.	to 11. Inject	ft.	
sw			water supply	7. Lawn a	nd garden only	9. Dewaterin	12. Other (Spe		
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well									
S		ological sample submitted t	to Department?	YES	NO		hat mo/day/yr wa	•	
5 TYPE OF CASING USED	submitted				/ater Well Disinfe		YES N		
O	; RPM (SR) 5. Wrought I	ron 7. Fibergla	00	her (Specify	below) CASI	NG JOINTS: C		Threaded Clamped	
	ABS 6. Asbestos-	-Cement 8. Concrete	_{e tile} SDI	R-26			vveided	Ciamped	
Blank casing diameter	5 in. to 4	40 ft., Dia.	in.	to	ft., D	ia. i	n, to	ft.	
Casing height above land surface	ce: 12 in.,	Weight:	2.35 lb	os. / ft.	Wall thic	kness or gaug	e No214		
TYPE OF SCREEN OR PERFO	RATION MATERIAL:								
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS						er (specify)			
2. Brass 4. Galvanize	ed 6. Concrete Ti	le 8. RMP (SR	R) 10. A	sbestos-Cem	nent 12. Non	e used (open l	hole)		
SCREEN OR PERFORATION O									
1. Continuous slot 3	. Mill slot 5. G	auzed wrapped	7. To	rch cut	9. Drille	d holes	11. None (or	oen hole)	
2. Louvered shutter 4	. Key punched 6. V	Vire wrapped	8. Sa	w cut	10. Other	(specify)			
SCREEN - PERFORATION INTE	ERVAL From	40 ft.	to 114	ft.,	From	ft.	to	ft.	
	From	ft.	to .	ft.,	From	ft.	to	ft,	
GRAVEL PACK INTER\	/ALS: From	24 ft.	to 114	ft.,	From	ft.	to	ft.	
	From	ft.	to	ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									
Grout Intervals: From	4 ft. to	24 ft., From	n ft.	to	ft.,	From	ft. to	ft.	
What is the nearest source of possible contamination: 1. South tank 4. Lateral lines 7. Pit privy			10. Livestoc). Livestock pens		13. Insecticide storage		15. Oil well/Gas well	
1. Septic tank 4. Lateral lines			11. Fuel sto	1. Fuel storage		•		. Other (specify below)	
2. Sewer lines 0. 0033 1001									
3 Watertight sewer line 6 Direction from well? West	. acabaga bir	i cca yara	i L. i Oi tiii LO	o to ago	How mar	ny feet? 10 f	t. plus		
From To	LITHOLOGIC	LOG	From	То		<u> </u>	GIC LOG	~	
0 3 topsoil									
3 12 clay	_							***************************************	
12 114 gray sh	ale								
						namePro		***************************************	
		*						***************************************	
					,				
						·			
				<u> </u>	-			**************************************	
	**************************************			-				W	
7	Le Constitue d'action de la constitue de la co					luance!	under pour livel e di sit	on or d	
Contractor's or Landowner	0/08/00/1			constructed			under my jurisdicti	on and	
was completed on (mo/day/ye	•			•	knowledge and b				
Kansas Water Well Contractor	r's License No. 236	This water	well record wa	is completed	on (mo/day/year	3/28	/2014		

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp