WATER WELL RECORD Form WWC-5 KSA 82a-1212 TOWNSHIP NUMBER SECTION NUMBER RANGE NUMBER LOCATION OF WATER WELL: SEdgwick BUTLER \mathbf{SW} NW27 1/4 1/4 SE 1/4 17 Т S **3E** E/W Distance and direction from nearest town or city street address of well if located within city? 713 Deerfield Ct. Andover, Kansas **GEARHART HOMES, Jim** WATER WELL OWNER: Board of Agriculture, Division of Water Resource 1111 N. Coachouse Ct. RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 100 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. ELEVATION: WITH AN "X" IN SECTION BOX: ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 26 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/9/14 Well water was Pump test data: ft. after hours of pumping @ gpm NW ΝE Est. Yield gpm Well water was ft. after hours of pumping @ gpm to 100 ⋾ Bore Hole Diameter 12 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SE SW 3. Feedlot 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample (NO Was a chemical/bacteriological sample submitted to Department? YES (YES NO submitted Was Water Well Disinfected? TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: C Glued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 50 to ft.. Dia. Dia ft. Blank casing diameter in. to in. to 12 2.35 Weight: lbs. / ft. Casing height above land surface: in., Wall thickness or gauge No .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 3. Stainless Steel 5. Fiberglass 1. Steel Concrete Tile 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE 7. Torch cut 9. Drilled holes 11. None (open hole) 3. Mill slot 5. Gauzed wrapped 1. Continuous slot 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 50 100 From to ft... From ft to ft. to From ft.. From ft. to 24 ft. 100 GRAVEL PACK INTERVALS: to ft., From From ft. ft. From to ft.. From ft to ft. **GROUT MATERIALS** Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 24 ft From ft ft., to ft. to From What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line South How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τо From To 0 topsoil 3 8 clay 95 8 gray shale 95 100limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 5/9/14 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/14/14
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb