WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER **Butler** \mathbf{SW} 1/4 NW1/4 SE 1/4 17 Т 27 S **3E** R Ε/W Distance and direction from nearest town or city street address of well if located within city? 601 Lake Crest Andover, Kansas H & H HOMEBUILDERS INC. WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 3906 N. Lakecrest Wichita, Kansas CITY, STATE: ZIP CODE Application Number: LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL 100 ft. **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/19/14 Pump test data: Well water was ΝW ΝE ft. after hours of pumping @ gpm Est. Yield: apm Well water was ft. after hours of pumping @ ø apm Ξ Bore Hole Diameter 12 to 100 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 5 40 in. to ft.. Dia. ft.. in. to Dia in. ft. to 12 Casing height above land surface: in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 1. Steel 2. Brass 6. Concrete Tile 8. RMP (SR) 4. Galvanized 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 4. Key punched 10. Other (specify) SCREEN - PERFORATION INTERVAL From 100 ft., to From ft. to From ft. to ft.. From to ft. 24 **GRAVEL PACK INTERVALS:** ft. to 100 From ft., From ft to ft. From ft to ft.. From to ft. **GROUT MATERIALS:** 1. Neat cement 2. Cement Grout Other bentonite hole plug 3. Bentonite Grout Intervals: From 4 ft 24 ft.. From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 11. Fuel storage 16. Other (specify below) 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 3 Watertight sewer line 6. Seepage pit Direction from well? How many feet? 10 ft. plus From Τо ITHOLOGIC LOG From To LITHOLOGIC LOG tonsoil 10 clay 3 10 98 grey shale 98 100limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 5/19/14 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/21/14 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb