Form WWC-5 WATER WELL RECORD KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER **Butler** SW 1/4 NW1/4 SE 1/4 17 т 27 S **3E** E/W R Distance and direction from nearest town or city street address of well if located within city? 821 N. Fairoaks Ct. Andover, Kansas H & H HOMEBUILDERS INC. WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 3906 N. Lakecrest Wichita, Kansas CITY, STATE: ZIP CODE Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 84 ft. **ELEVATION:** ft. Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 1/8/15 Pump test data: Well water was ft. after hours of pumping @ NW NE gpm Est. Yield: apm Well water was ft. after hours of pumping @ Φ aom ≅w Bore Hole Diameter 12 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering - SE-5. Public water supply 7. Lawn and garden only SW 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES 5 TYPE OF CASING USED CASING JOINTS: Glued 9. Other (Specify below) Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 40 Dia. Blank casing diameter in. to ft. to ft . Dia in. ft. to Casing height above land surface: Weight: lbs. / ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 40 From 84 ft to From ft. From to ft.. From ft. ft. GRAVEL PACK INTERVALS: 24 to From ft.. From ft to ft. ft. From to ft., From ft. to ft. **GROUT MATERIALS:** 6 1. Neat cement 2. Cement Grout Other bentonite hole plug 3. Bentonite Grout Intervals: 4 ft. 24 From ft... From to ft. ft., From What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 2. Sewer lines 5. Cess Pool 14. Abandon water well 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit How many feet? 40 ft. plus Direction from well? From LITHOLOGIC LOG LITHOLOGIC LOG Τо From Τо 0 topsoil 3 6 clay brown shale 6 35 35 84 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed under my jurisdiction and

1/8/2015

was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year)

1/9/2015

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb