Form WWC-5 WATER WELL RECORD KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER **Butler** SE NE SW 7 27 1/4 1/4 1/4 Т S **3E** R E/W Distance and direction from nearest town or city street address of well if located within city? 714 Gatewood Andover, Kansas ROBL CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource 5042 W. 21st RR#,ST. ADDRESS,BOX #: ZIP CODE: 67205 Wichita, Kansas CITY, STATE: Application Number .116 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION ft WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 46 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 3/18/15 Pump test data: Well water was NW ft. after hours of pumping @ ΝE apm Est. Yield: Well water was ft. after gpm hours of pumping @ gpm ≌ 12 to 116 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering S₩ SE 5. Public water supply 7. Lawn and garden only 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO Was Water Well Disinfected? submitted (YES) 5 TYPE OF CASING USED: CASING JOINTS: Glued 9. Other (Specify below) Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 Blank casing diameter in. to 50 Dia ft., Dia to in. to ft. 12 2.35 Casing height above land surface: in Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 5. Fiberglass 9. ABS 1. Steel 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 8. Saw cut 6. Wire wrapped 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 50 116 ft. From to ft., From ft ft. to From ft. to ft., From ft. ft. to 24 116 **GRAVEL PACK INTERVALS:** to From ft., From ft. ft. From ft. to ft., From ft. to ft. 6 **GROUT MATERIALS:** Other 2. Cement Grout bentonite hole plug 1. Neat cement 3. Bentonite Grout Intervals: From 24 ft.. ft. ft. From ft to What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 12. Fertilizer storage ③ Watertight sewer line 6. Seepage pit 9. Feed yard West Direction from well? How many feet? 20 ft. plus LITHOLOGIC LOG LITHOLOGIC LOG From Τо From Τo topsoil 20 clay 20 112 gray shale 112 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed under my jurisdiction and

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdict was completed on (mo/day/year) 3/18/2015 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/20/15 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp