		WATER W	ELL RECOR	D Fo	rm WV	/C-5 K	SA 82a-12	12		
1 LOCATION OF WATE	R WELL:	FRACTION			SECT	TION NUMBE	1	NUMBER	RANGE N	UMBER
Butler		NW 1/4			1/4	18	T 2	7 s	R 31	E E/W
Distance and direction from				?						
708 Deerfield		over, Kansas								
2 WATER WELL O		ESTYLE HO						Depart of Acres	authura Division of V	V-t D
RR#,ST. ADDRESS		S. Ridge Ro	ad					Board of Agric	culture, Division of V	vater Resource
CITY,	STATE: Wich	nita, Kansas			ZII	P CODE: 6	7209	Application Num	nber:	
3 LOCATE WELL'S LO	CATION 4	DEPTH OF COM	PLETED WELL:	90	ft.		ELEVATION:			
WITH AN "X" IN SEC	CTION BOX: Dec	oth of groundwate	er Encountered:		ft.			ft.		ft.
		ELL'S STATIC W		28 F	ET BELO	W I AND SI	JRFAÇE MEASI	IRED ON mo/d	av/vr: 3/1*	7/15
	NE			Well water		W LAND O	ft, after		of pumping @	gpm
1 1	NE	Est. Yield:	•	Well water			ft, after		of pumping @	gpm
w <u>≅</u> w	F B	ore Hole Diamete	J, 4.5	TTCII WAICI	to 9	0 ft		in.	to	ft.
- ×		ELL WATER TO I			.0 >		. 4114		44.1.	ction well
sw				ublic wate	r supply	7. Lawn	and garden onl	⊳ ^{9. Dewaterir}	'9 ·	pecify below)
	2	. Irrigation 4	. Industrial 6. Oi	il field wat	er supply	8. Air co	nditioning	10. Monitorin		poony bolon,
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	w	as a chemical/bacte	eriological sample subr			YES	NO	; If yes, v	vhat mo/day/yr v	was sample
	sul	bmitted				Was \	Water Well Disin	fected?	YES	NO
5 TYPE OF CAS		5. Wrough	t Iron 7. Fib	erglass	9. Ot	ther (Specify	y below) CAS	ING JOINTS: (Glued	Threaded
1. Steel	3. RPM (SF	₹) -		•	SDI	R-26			Welded	Clamped
2. PVC	> 4. ABS	6. Asbesto		ncrete tile	551	20				
Blank casing diameter	er 5	in. to	40 ft.,	Dia.	in.	to	ft.,	Dia. i	n. to	ft.
Casing height above	e land surface:	12 in.,	Wei	ght: 2	.35 It	os. / ft.	Wall th	ickness or gaug	e No214	
TYPE OF SCREEN	OR PERFORATION	MATERIAL:		_						
1. Steel 3	3. Stainless Steel	Fiberglass	7. PV	>	9. Al	BS	11. Ot	her (specify)		
2. Brass 4	I. Galvanized	Concrete	Tile 8. RM	P (SR)	10. A	sbestos-Ce	ment 12. No	ne used (open	hole)	
SCREEN OR PERFO	RATION OPENING	GS ARE:								
1. Continuous slot			Gauzed wrapped		7. To i	rch cut	9. D rill	ed holes	11. None (d	open hole)
2. Louvered shutte	A Kayan		Wire wrapped		(8. Sa		10 046	er (specify)	·	
2. Louvered shalle	er 4. Key pu	unched 0.	• •			W CUI	10. Oth	er (Specify)		
SCREEN - PERFORA	ATION INTERVAL	From	40 ft.	to	90	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PA	CK INTERVALS:	From	24 ft.	to	90	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERI	ALS: 4 Noot		2 Compat Com	4						
Conditional State of the State									_	
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to What is the nearest source of possible contamination:								ft.		
1. Septic tank	4. Lateral	-	7. Pit privy	10.	Livestoc	k pens	13. Insect	cide storage	15. Oil well/0	Sas well
2. Sewer lines	5. Cess P	Pool 60°	B. Sewage lagoon	11.	. Fuel stor	rage	14. Aband	on water well	16. Other (sp	ecify below)
l			9. Feed yard	12.	. Fertilizer	storage				
O Watertight sewer Direction from well?	South	ae bir	, and				How ma	any feet? 10 f	t. plus	
From To		LITHOLOGI	CLOG	T	From	То		LITHOLO		
0 3	topsoil		<u> </u>		7 10711	<u>'</u> -		LITTIOLO	CIO LOC	
3 10	clav									
10 87	gray shale							17 111111		
87 90	limestone									
-										
						 				
	 									
									*	
 	 					 				
				- +						
<u> </u>	†			-						
7 Contractor's or i	andowned Oct	notion. This		1	\		d or ^	nlugged	indor my indicated	ion and
	Landowner's Certific		_			constructed			under my jurisdict	ion and
was completed on	(mo/day/year)	3/17/2015	and this	s record is	true to the	best of my	knowledge and	oelief.		
Kansas Water Well	Contractor's Licens	se No. 236	This	water well	record wa	s completed	d on (mo/day/yea	ar) 3/13	8/15	
under the business name of Harn Well and Pump Service by (signature)										
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp										