WATER WELL RECOR	RD Form WV	VC-5 K	SA 82a-12 ⁻	12		
1 LOCATION OF WATER WELL: FRACTION		SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER				
Butler NE 1/4 NW 1/4	SE 1/4	6	T 2	7 s	R 3E	E/W
Distance and direction from nearest town or city street address of well if located within city 703 W. Sandstone Ct. Andover, Kansas	?					
703 W. Sandstone Ct. Andover, Kansas 2 WATER WELL OWNER: ECKHOFF, Chris						
RR#,ST. ADDRESS,BOX #: 703 W. Sandstone Ct.				Board of Agri	culture, Division of Wa	ter Resource
CITY, STATE: Andover, Kansas	ZI	P CODE:		Application Num	nber:	
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL:	115 ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered:	ft.			ft.		ft.
WELL'S STATIC WATER LEVEL	55 FT. BELO	W LAND SU	RFACE MEASU	JRED ON mo/d	lay/yr: 4/28/]	
Pump test data:	Well water was		ft. after		of pumping @	gpm
<u>⊕</u> Est. Yield: gpm	Well water was		ft. after	hours	of pumping @	gpm
Est. Yield: gpm Bore Hole Diameter 12 in.	. to 1	15 ft.	and	in.	to	ft.
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Pr	ublic water supply	C7 Lawn a	nd garden only	9. Dewaterii	•	
	il field water supply			10. Monitorin	12. Other (Spe	cify below)
S Was a chemical/bacteriological sample sub		YES	NO		what mo/day/yr wa	s sample
submitted		Was W	ater Well Disint	ected? (YES NO)
TYPE OF CASING USED: 5. Wrought Iron 7. Fil	iberglass 9. O	ther (Specify	below) CAS	ING JOINTS: (Glued T	hreaded
1. Steel 3. RPM (SR) 2. PVC 4. ABS 6. Asbestos-Cement 8. Co	oncrete tile SD	R-26			Welded (Clamped
2.FVC 4.AB3	Dia. in.	to	4	Dia :		4
12					in. to	ft.
Casing height above land surface: 12 in., Wei TYPE OF SCREEN OR PERFORATION MATERIAL:	eight: 2.35 II	os. / ft.	Wall th	ickness or gaug	ge No214	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)						
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. To	rch cut	9. Drill	ed holes	11. None (ope	en hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	(8. Sa	w cut	10. Othe	er (specify)		,
	44.5					
		ft.,	From	ft.	to	ft.
From ft. GRAVEL PACK INTERVALS: From 24 ft.	to to 115	ft.,	From -	ft.	to	ft.
Troili		ft.,	From	ft.	to	ft.
From ft.	to	ft.,	From	ft.	to	ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Gro	_	Bentonite			onite hole plug	
Grout Intervals: From 4 ft. to 24 ft., What is the nearest source of possible contamination:	From ft.	to	ft.,	From	ft. to	ft.
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestoc	k pens	13. Insecti	cide storage	15. Oil well/Gas	well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)						
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage						
Direction from well? West			How ma	ny feet? 25 f		
From To LITHOLOGIC LOG	From	То		LITHOLO	GIC LOG	
0 3 topsoil 3 20 clay		ļ .				
20 110 grey shale						
110 115 limestone						
			······		-	
7 Contractor's or Landowner's Certification: This water well was 1, Contractor's or Landowner's Certification:	structed 2 rec	constructed	or 3. p	olugged u	under my jurisdiction	and
was completed on (mo/day/year) 4/28/2015 and this record is true to the best of my knowledge and belief.						
under the business name of Harp Well and Pump Service by (signature)						