WATER WELL R Original Record		WWC-5 ge in Well Use		ision of Water urces App. No		Well ID
1 LOCATION OF W		Fraction		tion Number	······································	
County: Bu-	fler	NE'SE " NW"	1/4	<u> </u>	T ZA S	R Z ME □ W
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and						
Business: Address: Address: Address: Address: Business: Address: Addre						
Address:						
City:	State:	ZIP:			ver, vs.	61002
3 LOCATE WELL WITH "X" IN	4 DEPTH OF CO	MPLETED WELL: .	95 . ft.	5 Latitud	le:	(decimal degrees)
SECTION BOX:	Depth(s) Groundwater		Longitude:(decimal degrees)			
N		3) ft., or 4)		Datum: WGS 84 NAD 83 NAD 27		
	WELL'S STATIC WATER LEVEL:			Source for Latitude/Longitude:		
NW NE				☐ GPS (unit make/model:) (WAAS enabled? ☐ Yes ☐ No)		
	Pump test data: Well water was ft.			☐ Land Survey ☐ Topographic Map		
W	after hours pumping gpm Well water was ft.			Online Mapper:		
SW SE		s pumping			** *** *** *** ** *** *** *** *** ***	
	Estimated Yield:gpm			6 Elevation:ft. Ground Level TOC		
S				Source:		
1 mile						
1. Domestic: 5. Public Water Supply: well ID 10. Oil Field Water Supply: lease						
☐ Household	6. Dewatering: how many wells?			11. Test Hole: well ID		
🔀 Lawn & Garden	7. 🔲 Aquifer F		☐ Cased ☐ Uncased ☐ Geotechnical			
Livestock	8. Monitori		12. Geothermal: how many bores?			
2. ☐ Irrigation 3. ☐ Feedlot				a) Closed Loop ☐ Horizontal ☐ Vertical b) Open Loop ☐ Surface Discharge ☐ Inj. of Water		
4. Industrial	☐ Recovery		Auacuon			
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☑ No If yes, date sample was submitted:						
Water well disinfected? ∰ Yes □ No						
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: I Glued Clamped Welded Threaded						
Casing diameter						
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No						
☐ Steel ☐ Stainless Steel ☐ Fiberglass PVC ☐ Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)						
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From □ ft to − ft From −						
SCREEN-PERFORATED INTERVALS: From						
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From						
Grout Intervals: From						
Nearest source of possible contamination:						
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage ☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well						
Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well						
Other (Specify)						
Direction from well?	LITHOLO	Distance from we	FROM		it.	PLUGGING INTERVALS
O I	70P 50		FROM	10 1	ATTO. LOG (CODE.) OF	FLUGGING INTERVALS
1 13	chv					
13 20	Thate					
20 30	limestone.					
30 95	<u>Shale</u>		1			
			Notes:			
110163.						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged						
under my jurisdiction and was completed on (mo-day-year)						
under the business name of						
INSTRUCTIONS: Send one copy to WATER WELL OWNER and retain one copy for your records. Submit fee of \$5.00 for each constructed well along with one (white) copy to Kansas						
Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone (785) 296-3565.						
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 9/10/2012						