WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW 1/4 **Butler** NW1/4 NE 1/4 17 Т 27 S **3E** E/W Distance and direction from nearest town or city street address of well if located within city? Andover, Kansas 807 N. Fairoaks Place H & H HOMEBUILDERS INC. WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 3906 N. Lakecrest Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: WITH AN "X" IN SECTION BOX ft. Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 26 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 6/28/16 Pump test data: Well water was ft. after NE hours of pumping @ NW apm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Ξ Bore Hole Diameter 12 to 100 and WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 1. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted (YES) Was Water Well Disinfected? TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter to 50 ft.. Dia. to ft.. Dia to ft. 12 Casing height above land surface: 2.35 Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1. Steel 2. Brass 4. Galvanized 6. Concrete Tile RMP (SR) 12. None used (open hole) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 4. Key punched 10. Other (specify) SCREEN - PERFORATION INTERVAL 100 From to ft., From ft. to From ft. to ft.. From to ft. **GRAVEL PACK INTERVALS:** 24 100 From ft.. From ft. From ft. tο ft.. From ft. to ft. **GROUT MATERIALS:** 2. Cement Grout Other bentonite hole plug 1. Neat cement 3. Bentonite Grout Intervals: From 4 ft. 24 ft.. From ft. to ft.. From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed vard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit How many feet? 40 ft. plus Direction from well? From Τo LITHOLOGIC LOG From To LITHOLOGIC LOG O tonsoil 3 8 clay 8 65 brown shale 65 100 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and

was completed on (mo/day/year) 6-28-16 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/29/16

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb