| WATER WELL RECORD F | orm WWC-5 KSA 8 | 82a-1212 | |
|---|---|-------------------------|-------------------------------------|
| 1 LOCATION OF WATER WELL: FRACTION | SECTION NUMBER | TOWNSHIP NUMBER | RANGE NUMBER |
| Butler NE 1/4 NE 1/4 SW | 1/4 6 | т 27 S | R 3E E/W |
| Distance and direction from nearest town or city street address of well if located within city? | | | |
| 2327 N. Lakeview Ct. Andover, Kansas | | | |
| 2 WATER WELL OWNER: BLUE CUSTOM HOMES LLC | | | |
| RR#,ST. ADDRESS,BOX #: 106 S. Breezy Pointe Circle | | Board of Agric | ulture, Division of Water Resource |
| CITY, STATE: Wichita, Kansas | ZIP CODE: | Application Num | ber: |
| 3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 10 | 0 ft. ELE | VATION: | |
| WITH AN "X" IN SECTION BOX: | ft. | ft. | ft. |
| | | | |
| | FT. BELOW LAND SURFAC | | |
| Pump test data: Well wat | | | of pumping @ gpm |
| Est. Yield: gpm Well wat Bore Hole Diameter 12 in. | | | of pumping @ gpm |
| | to 100 ft. | and in. | to ft. |
| WELL WATER TO BE USED AS: | Town and m | 9. Dewaterir | ng 11. Injection well |
| | er supply 7. Lawn and ga | | 12. Other (Specify below) |
| 2. Irrigation 4. Industrial 6. Oil field w | | <u> </u> | g well /hat mo/day/yr was sample |
| S Was a chemical/bacteriological sample submitted to D submitted | | Well Disinfected? | YES NO |
| | was water | | \geq |
| 5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass | 9. Other (Specify below | v) CASING JOINTS: C | Glued Threaded |
| 1. Steel 3. RPM (SR) 2. RVC 4 ARS 6. Asbestos-Cement 8. Concrete til | SDR-26 | | Welded Clamped |
| 2. FVC 4. ADS | - | | |
| Blank casing diameter 5 in. to 50 ft., Dia. | in. to | ft., Dia. i | n, to ft. |
| Casing height above land surface: 12 in., Weight: | 2.35 lbs. / ft. | Wall thickness or gaug | e No214 |
| TYPE OF SCREEN OR PERFORATION MATERIAL | | | |
| 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC | 9. ABS | 11. Other (specify) | |
| 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) | 10. Asbestos-Cement | 12. None used (open l | nole) |
| | | | , |
| SCREEN OR PERFORATION OPENINGS ARE: | | | |
| 1. Continuous slot 3. Mill slot 5. Gauzed wrapped | 7. Torch cut | 9. Drilled holes | 11. None (open hole) |
| 2. Louvered shutter 4. Key punched 6. Wire wrapped | 8. Saw cut | 10. Other (specify) | |
| SCREEN - PERFORATION INTERVAL From 50 ft. to | 100 ft., F | | |
| | | rom ft. | to ft. |
| From ft. to | ft., F | rom ft. | to ft. |
| GRAVEL PACK INTERVALS: From 40 ft. to | 100 ft., Fi | rom ft. | to ft. |
| From ft. to | ft., F | rom ft. | to ft. |
| | | | |
| 6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout | 3. Bentonite | Other bent | onite hole plug |
| Grout Intervals: From 4 ft. to 24 ft., From | ft. to | ft., From | ft. to ft. |
| What is the nearest source of possible contamination: | 0. Livestock pens | 13. Insecticide storage | 15. Oil well/Gas well |
| 1. Septic talik 4. Laterar mies | | 5 | 16. Other (specify below) |
| | | 14. Abandon water well | to: outer (specify below) |
| 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage | | | |
| Direction from well? East | | How many feet? 50 f | - |
| From To LITHOLOGIC LOG | From To | LITHOLO | GIC LOG |
| 0 3 topsoil | | | |
| 3 30 clay | | | |
| 30 95 gray shale | | | |
| 95 100 limestone | | | |
| | | | |
| | | | |
| | | | |
| | | · · · · | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| 7 Contractor's or Landowner's Certification: This water well was 1 Constructed | 2 reconstructed 0 | r 3 pluaged u | under my jurisdiction and |
| 7 Contractor's or Landowner's Certification: This water well was 1. constructed | | | under my jurisdiction and |
| | 2. reconstructed o s true to the best of my knowl | | under my jurisdiction and |
| was completed on (mo/day/year) 8/29/2016 and this record i | | edge and belief. | under my jurisdiction and |
| was completed on (mo/day/year) 8/29/2016 and this record i | s true to the best of my knowl | edge and belief. | /2016 |