		WATERW	ELL REC	ORD F	orm WV	<u>VC-5 r</u>	SA 82a-12	12		
1 LOCATION OF WATE	R WELL:	FRACTION	N. 1707			TION NUMBE		P NUMBER	RANGE N	
Butler		NE 1/4	·	/4 SW	1/4	6	T 2	7 s	R 31	≗ E/W
Distance and direction from nearest town or city street address of well if located within city?										
2306 N. Lake			dover, Ka							
2 WATER WELL	OWNER: \mathbf{BLU}	E CUSTOM	HOMES	LLC				B		B
RR#,ST. ADDRESS		5. Breezy Poi	nte Circle					Board of Agri	culture, Division of V	vater Resource
CITY,	STATE: Wich	iita, Kansas			Z	IP CODE:		Application Num	nber:	
3 LOCATE WELL'S LO		DEPTH OF COM	PLETED WEL	L: 10	00 ft.		ELEVATION:			
WITH AN "X" IN SEC	CTION BOX: Dep	oth of groundwate	er Encountere	d:	ft			ft.		ft.
		ELL'S STATIC W		40	ET BELC	אין שארו אינ	JRFACE MEASI	IRED ON moto	lav/vr: 9/3 1	1/16
			ımp test data:			ATT EXITE O	ft. after		of pumping @	-
NW -	NE-	Est. Yield:	•	Well wa			ft, after		of pumping @	gpm
w Z		ore Hole Diamete	gpm r 12	in.	to 1	100 ft		in,	to	gpm ft.
= "		ELL WATER TO E	•		10 1		. and		44.1.	ction well
Sw -			. Feedlot	5. Public wa	ter supply	Z. Lawn	and garden only	⊳9. Dewaterii		pecify below)
			Industrial	6. Oil field v			nditioning	10. Monitorir		pecily below)
		as a chemical/bacte				YES	(NO)		vhat mo/day/yr	was sample
		bmitted	,				Water Well Disin	fected?	YES	NO
5 TYPE OF CAS	SING USED:	E \\/	t Iron	7. Fiberglass	9 0	ther (Specit	/ below) CAS	SING JOINTS: (Glued	Threaded
1. Steel	3. RPM (SR	₹) 5. Wrough	t IIOII	•	SD.	٠.	, ,		Welded	Clamped
2. PVC	> 4. ABS	6. Asbesto	s-Cement	8. Concrete t	ile SD	R-26				
Blank casing diameter	er 5	in. to	40 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing beight above	land surface:	12 _{in}		Weight:	2.35	bs. / ft.	Wall th	nickness or gaug	1e No. 214	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:										
1	3. Stainless Steel	5. Fiberglass		7. PVC	9. A	BS	11. 01	her (specify)		
1	Galvanized	6. Concrete	_	B. RMP (SR)	10 A	sbestos-Ce		one used (open	hole)	
				5. F(IIII (G)(I)	10.7	13003103-00	72.11	one acca (open	11010)	
SCREEN OR PERFO										
1. Continuous slot 3. Mill slot 5. Gauzed wrapped					7. To	7. Torch cut 9. Drilled holes 11. None (open hole)				
2. Louvered shutte	er 4. Key pu	unched 6.	Wire wrappe	d	(8. S a	w cut	10. Oth	er (specify)		
SCREEN - PERFORA	ATION INTERVAL	From	40 ft	. to	100	ft.,	From	ft.	to	ft.
		From	ft			ft.,	From			
ODAVEL DA	OK INTERVALO.		24 ft.			•		ft.	to	ft.
GRAVEL PA	CK INTERVALS:	From			100	ft.,	From	ft.	to	ft.
		From	ft.	. to)	ft.,	From	ft.	to	ft.
6 GROUT MATER	IALS: 1. Neat o	cement	2. Cemer	nt Grout	;	3. Bentonite	•	Other bent	onite hole pl	ug
									ft.	
What is the nearest source of possible contamination:							15. Oil well/0	2 ···-!!		
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens						is. insect	icide storage			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)										
3. Watertight sewe	er line 6. Seepag	ge pit 🤄	9. Feed yard		12. Fertilize	r storage				
Direction from well?	West						How m	any feet? 60 1		
From To		LITHOLOGI	C LOG		From	То		LITHOLC	GIC LOG	
0 3	topsoil					ļ				
3 12	clay				ļ					
12 45	brown shale				-	<u> </u>				
45 95	gray shale				 	 	ļ			
95 100	limestone				 	 				
 	 				+					
	 				1					
					1	1				
	1					1				
					1	1				
					1	1				
					1	1				
					1		į	,		
7 Contractor's or	l andowner's Certific	cation: This water	rwell was 1 (constructo	1) 2 "	constructe	d or 3.	plugged	under my jurisdic	tion and
0.01/0.01/										
was completed on	(mo/day/year)	0/31/2010	o ar			•	-			
Kansas Water Well	l Contractor's Licens	se No. 236		This water w	ell record wa	as complete	d on (mo/day/yea	er) 9/2/	2016	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp										
1	h		r ~ ~ · · · · ·	-		•	1 (uwws	. ILWIL	,