WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Butler SW1/4 \mathbf{SW} NE 6 27 1/4 1/4 Т S 3E Ε/W Distance and direction from nearest town or city street address of well if located within city? 2352 N. Silverdale Andover, Kansas **BLUE CUSTOM HOMES LLL** WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX # 106 S. Breezy Pointe Circle ZIP CODE: 67235 Wichita, Kansas CITY, STATE: Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 110 Depth of groundwater Encountered: ft. fŧ ft. WELL'S STATIC WATER LEVEL 38 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 2/14/17 Pump test data: Well water was NW NE ft. after hours of pumping @ apm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm ≅ ∨ Bore Hole Diameter 12 to 110 and ft. WELL WATER TO BE USED AS 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample s Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES 5 TYPE OF CASING USED CASING JOINTS: Glued 9. Other (Specify below) Threaded 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 5 Blank casing diameter 50 ft.. Dia. to ft.. Dia ft. in to 12 Casing height above land surface: 2.35 Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE 3. Mill slot 1 Continuous slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 50 From to 110 ft . From ft. to From to ft.. From ft. ft. **GRAVEL PACK INTERVALS:** 24 From to 110 ft.. From ft to ft. From ft. ft.. to From to ft. **GROUT MATERIALS:** 6 1. Neat cement 2 Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft 24 ft From ft. From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3 Watertight sewer line West How many feet? 10 ft. plus Direction from well? F<u>rom</u> Τо LITHOLOGIC LOG From То LITHOLOGIC LOG 3 topsoil 3 10 clay 10 35 brown shale 35 105 gray shale 105 110 limestone

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 2/14/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

Todd S. Harb