WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER SW $\mathbf{SW}$ Butler 1/4 NE 1/4 6 Т 27 S **3E** E/W Distance and direction from nearest town or city street address of well if located within city? 2338 N. Lake Side Circle Andover, Kansas WATER WELL OWNER: **SHARP HOMES** Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 2131 N. Collective Ste. #A ZIP CODE: 67206 CITY, STATE: Wichita, Kansas Application Number: 80 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL WITH AN "X" IN SECTION BOX Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 38 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was NW ΝE ft. after hours of pumping @ apm Est. Yield: hours of pumping @ apm Well water was ft. after gpm Ξ Bore Hole Diameter 12 80 and in. ft WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 5. Public water supply 7. Lawn and garden only 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? S YES CNO submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 2. PVC 6. Asbestos-Cement 8. Concrete tile 4. ABS 5 40 Blank casing diameter Dia. in. to ft., Dia ft in to 12 Casing height above land surface in Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 40 ft. 80 From to ft. From to ft. ft. From to ft.. From to ft. 24 GRAVEL PACK INTERVALS: ft. to 80 From ft., From to ft From ft. ft., From ft. 6 **GROUT MATERIALS** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 24 ft. From ft to ft.. From to ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3 Watertight sewer line 6. Seepage pit Direction from well? South How many feet? 10 ft. plus From To LITHOLOGIC LOG From To LITHOLOGIC LOG topsoil 10 clay 10 40 brown shale 40 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 2/15/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/17/17 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp