

W	_		RECORD		WWC-5 1353			ion of Wate						
	Original Record Correction Change in Well Use					Resources Ap			1					
1	LOCATION OF WATER WELL: Fraction						-				nge Number			
2	County		·		1/4 1/4 1/4		Daras	$\begin{array}{c c c c c c c c c c c c c c c c c c c $						
2	WELL Business: Address: Address: City:	OWNER:	State:	First: ZIP:	Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:									
3	LOCAT	E WELL				6								
-		4 DEPTH OF COMPLETED WELL: .							5 Latitude:					
	SECTIO			Depth(s) Groundwater Encountered: 1) ft. 2) ft. 3) ft., or 4) \Box Dry We					Longitude:					
	N	WELL'S STATIC WATER LEVEL: ft.								Source for Latitude/Longitude:				
	\downarrow		yr)		GPS (unit make/model:)									
	NW	NE			, measured on (mo-day-			(WAAS enabled? 🗌 Yes 🔲 No)						
w		ı	- 6	Pump test data: Well water was ft. after hours pumping gpm					□ Land Survey □ Topographic Map □ Online Mapper:					
vv	I	· · · ·		Well water was ft.										
	SW	SE		after hours pumping gpm										
		Estimated Yield:gpm						6 Elevation :ft. □ Ground Level □ TOC Source: □ Land Survey □ GPS □ Topographic Map						
	S Bore Hole Diameter: in. to in. to in. to													
	7 WELL WATER TO BE USED AS:													
1. Domestic: 5. Dublic Water Supply: well ID 10. Oil Field Water Supply: lease														
	House			6. Dewatering: how many wells?				11. Test Hole: well ID						
	_	Lawn & Garden 7. 🗌 Aquifer Recharge: well ID												
	Livesto			g: well ID al Remediation: well II										
	☐ Feedlo		Air Sparge	Extraction		b) Open Loop Surface Discharge Inj. of Water								
4.	🗌 Industr	ial		Recovery				13. Other (specify):						
W	Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:													
	Water well disinfected? Yes No													
	8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded													
	Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.													
	Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No													
1.	I YPE OF SCREEN OR PERFORATION MATERIAL: Steel Fiberglass PVC Other (Specify)													
	Brass Galvanized Steel Concrete tile None used (open hole)													
SC	SCREEN OR PERFORATION OPENINGS ARE:													
	□ Continuous Slot □ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify) □ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)													
SC					ne wrapped Sa						ft to	, ft		
50														
GRAVEL PACK INTERVALS: From ft. to ft., From ft., From ft., From ft. to ft. o ft. o ft. o ft. o ft. to ft. to ft. to ft. to ft. o ft. to ft. ft. to ft. ft. to ft. ft. ft. ft. ft. ft. ft. ft. ft.														
Gr	out Interva	als: From	ft. to		ft., From									
		-	ible contaminati		□ D': D :		— т	·			1.0			
	□ Septic ′ □ Sewer I			Lateral Line Cess Pool	es 🗌 Pit Privy 🗌 Sewage La	goon		ivestock Pe uel Storage		☐ Insectici ☐ Abandor				
		ght Sewer			☐ Feedyard	5001		ertilizer Sto						
	Other (Specify)			••••••				-					
	rection fro FROM				Distance from we	FRON				ft. HO. LOG (cont.) or I				
10	FROM	TO		ITHOLOG	JU LUG	FROM	VI	10	LII	HO. LOG (cont.) of I	PLUGGIN	GINTERVALS		
			1											
			1											
														
		Notes:												
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged														
under my jurisdiction and was completed on (mo-day-year) and this record is true to the best of my knowledge and belief.														
Ka	ansas Wa	ter Well C	ontractor's Lice	ense No	This Wa	ater Well	Reco	rd was cor	mple	ted on (mo-day-yea	ar)	-		
under the business name of														
I	Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.													
	-		lheks.gov/waterwel									SA 82a-1212		