WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER SW 1/4 **Butler** \mathbf{sw} 1/4 NE 1/4 6 27 Т S 3E E/W Distance and direction from nearest town or city street address of well if located within city? 704 W. Sandstone Ct. Wichita, Kansas KLAUSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10008 W. York ZIP CODE: 67215 Wichita, Kansas CITY, STATE: Application Number: 4 DEPTH OF COMPLETED WELL: 110 ELEVATION: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft ft. ft. WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/20/17 Pump test data: Well water was NW ΝE ft. after hours of pumping @ apm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Ξ Bore Hole Diameter 12 to 110 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 Blank casing diameter 50 Dia. to ft.. to ft Dia ft. to 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 4. Key punched 10. Other (specify) SCREEN - PERFORATION INTERVAL 110 From to ft From ft. to From ft. to ft.. From ft GRAVEL PACK INTERVALS: ft. 110 From ft.. From ft. ft. From to ft., From to ft **GROUT MATERIALS:** 2. Cement Grout Other bentonite hole plug 1. Neat cement 3. Bentonite Grout Intervals: From 4 ft 24 ft.. ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 11. Fuel storage 16. Other (specify below) 8. Sewage lagoon 2. Sewer lines 5. Cess Pool 14. Abandon water well 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit East How many feet? 50 ft. plus Direction from well? From Τо LITHOLOGIC LOG From To LITHOLOGIC LOG O topsoil 3 10 clay 10 40 brown shale 40 105 grey shale 105 110 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 10/20/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) Todd S. Harp under the business name of Harp Well and Pump Service by (signature)