	WATER WE	LL RECORD	Form WV		SA 82a-1212				
1 LOCATION OF WATER WELL:	FRACTION			TION NUMBER			RANGE NUME		
Butler	2 1/1	.,	E 1/4	6	Т 27	S	R 3E	E/W	
Distance and direction from nearest town or city street address of well if located within city?									
1338 W. Ledgestone Andover, Kansas NOEDER COUNSTRUCTION LLC MOEDER COUNSTRUCTION LLC									
Board of Agriculture, Division of Water Resource									
CITY, STATE: Wichita, Kansas ZIP CODE: 67209 Application Number:									
	4 DEPTH OF COMPLE	TED WELL:	110 ft.		ELEVATION:				
WITH AN "X" IN SECTION BOX:	Depth of groundwater E	ncountered:	ft.			ft.	1/31/1	8 ft.	
	WELL'S STATIC WATE	ER LEVEL 44	FT. BELO	W LAND SL	IRFACE MEASUR	RED ON mo/o	lay/yr:		
Pump test data: Well water was ft. after hours of pumping (gpm	
<u>o</u>	Est. Yield:	31	ll water was	_	ft. after	hours	of pumping @	gpm	
M Miles	Bore Hole Diameter	12 in.	to 1	. 0 ft.	and	in.	to	ft.	
SW - SE	WELL WATER TO BE	USED AS:	c water supply	€7. Lawn a	nd garden only	9. Dewateri	•		
	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
	2. Irrigation 4. Industrial 6. Oil field water supply 6. All conditioning Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample								
3	submitted	,			Vater Well Disinfe	cted?	YES NO		
5 TYPE OF CASING USED:	5. Wrought Ire	on 7. Fiberg	ılass 9. O	ther (Specify	below) CASII	NG JOINTS: (Glued Tr	readed	
1. Steel 3. RPM	(SR)		SD.	R-26			Welded C	lamped	
2. PVC 4. ABS	6. Asbestos-C	_	ete tile	20					
Blank casing diameter 5	in. to 5	() ft., Dia	. in.	to	ft., D	ia.	in. to	ft.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes						11. None (ope	n hole)		
2. Louvered shutter 4. Ke	y punched 6. Wi	re wrapped	(8. Sa	w cut	10. Other	(specify)			
SCREEN - PERFORATION INTERV	AL From	50 ft.	to 110	ft.,	From	ft.	to	ft.	
	From	ft.	to	ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS		24 ft.	to 110	ft.,	From	ft.	to	ft.	
GRAVEETAGRITICAL		ft.	to						
	From			ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well								well	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)									
Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? South How many feet? 30 ft. plus									
From To	LITHOLOGIC	LOG	From	То		LITHOLO	GIC LOG		
0 3 topsoil	*****								
3 12 clay				<u> </u>					
12 105 gray shale				<u> </u>					
105 110 limestone				<u> </u>				## At No.	
				†					

				†					
7 Contractor's or Landowner's Co	ertification: This water w	ell was 1 Constr	ucted 2 re	constructed	d or 3, p	lugged	under my jurisdiction	and	
1/01/10									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/6/18									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									
					, ,	7777	. 10001 P		