		WATERW	ELL REC	JORD 1	orm vv	WC-5 I	KSA 82a-1	212				
1 LOCATION OF WATE	ER WELL:	FRACTION	MYXX7	37557		CTION NUMBI	1	HIP NUMBER	1	NUMBER		
Butler		NW 1/4		1/4 NW	1/4	6	Т	27 s	R	3E E/V	<u>v</u>	
Distance and direction fro	-			in city?								
2645 N. Blue		Andover, I HAELLS, Jef										
2 WATER WELL RR#,ST. ADDRESS		naells, jei N. Bluestone	1					Board of Agri	iculture, Division o	of Water Res	ource	
1		over, Kansas			-	ZIP CODE:		Application Nun	nher:			
		DEPTH OF COMP	ETED WE	j. 9			ELEVATION					
3 LOCATE WELL'S L WITH AN "X" IN SE	CTION BOX:			<b>_L</b> .			ELEVATION				ft.	
N N		oth of groundwater				ft.		ft.			ι.	
	; I I	ELL'S STATIC WA				OW LAND S		SURED ON mo/o		30/18		
NW -	NE	Est. Yield:	np test data:	: Well wa Well wa			ft. after ft. after		s of pumping @ s of pumping @		gpn gpm	
w M	E   B/	ore Hole Diameter	gpm 12	in.	to	90 4	ft. and	in.	to		ft.	
[		ELL WATER TO B			10	,	it. and	9. Dewateri	44 5	jection we		
sw			Feedlot		ter supply	7. Lawn	and garden o	nly)	a	(Specify be		
	2	. Irrigation 4.	Industrial	6. Oil field v	ater supp	ly 8. Airco	onditioning	10. Monitorii	ng well			
s		/as a chemical/bacter	iological samp	le submitted to	Department?	YES	NO		what mo/day/y		ple	
5 705050		bmitted				Was	Water Well Dis	infected?	YES	NO		
5 TYPE OF CA	SING USED: 3. RPM (SR	5. Wrought	Iron	7. Fiberglass	9. (	Other (Speci	fy below) C	ASING JOINTS: (		Thread		
2. PVC	> 4. ABS	6. Asbestos	-Cement	8. Concrete t	ile SI	R-26			Welded	Clampe	ed	
Blank casing diamet	_		40 ft.,	Dia.		40	<b>64</b>	Dia	in 4-	4		
	_	10	40 n.,		in.	to	ft.,		in. to	ft		
Casing height abov		,		Weight:	2.35	lbs. / ft.	Wall	thickness or gaug	ge No2]	.4		
1	OR PERFORATION  3. Stainless Steel	5. Fiberglass	_	7. PVC	0	ABS	11	Other (specify)				
1	4. Galvanized	6. Concrete Ti	_	8. RMP (SR)		Asbestos-Ce		None used (open	halo)			
			iie	o. RIVIF (SR)	10.	ASDESIUS-CE	ement 12.	None used (open	noie)			
SCREEN OR PERFO									AA Nama			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped					7. T	orch cut	9. <b>D</b> i	9. Drilled holes 11. None ( open hole)				
2. Louvered shutt	er 4. Key pu	unched 6. V	Vire wrappe	ed	< 8. <b>S</b>	aw cut	10. O	ther (specify)				
SCREEN - PERFOR	ATION INTERVAL	From	<b>40</b> ft	. to	90	ft.,	From	ft.	to		ft.	
		From	ft	. to		ft.,	From	ft.	to		ft.	
GRAVEL PA	ACK INTERVALS:	From	<b>24</b> ft	. to	90	ft.,	From	ft.	to		ft.	
		From	ft	. to	,	ft.,	From					
C GROUT MATER	IAI C:				,			ft.	to		ft.	
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonit hole plu									•			
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to What is the nearest source of possible contamination:									iO	ft.		
							15. Oil we	I/Gas well				
<u> </u>						1. Fuel storage 14. Aban			idon water well 16. Other (specify below)			
3 Watertight sew		_	Feed yard		12. Fertilize	er storage						
Direction from well?	South	90 p	•			•	How	many feet? 10 f	ft. plus			
From To		LITHOLOGIC	LOG		From	То			GIC LOG			
0 3	topsoil											
3 20	clay											
20 45	brown shale											
45 90	grey shale				<u> </u>							
					+							
					<del> </del>	+	+					
		,										
			-11			1						
		· · · · · · · · · · · · · · · · · · ·			1							
Contractor's or	Landowner's Certific		well was 1.	constructed	) 2. r	econstructe	ed or 3.	plugged	under my jurisc	iction and		
was completed on	(mo/day/year)	3/30/18	ar	nd this record	is true to th	e best of my	y knowledge an	d belief.				
Kansas Water Wel	Contractor's Licens	se No. 236		This water we	ell record w	as complete	ed on (mo/day/y	ear) 4/6	6/18			
			n Carria						7/~	ħ		
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp												