		RECORD		WWC-5		ision of Water				
		Correction		e in Well Use		urces App. No.		Well ID		
				Fraction				ge Number		
	y: Butler			NE 1/4 NW 1/4 SE 1/		7 T 27 S R 3 ■ E □ W				
2 WELL				First:		Street or Rural Address where well is located (if unknown, distance and				
	Sharp Ho	omes llective Lane			direction from nearest town or intersection): If at owner's address, check here:					
Address:	2131 00	liective Lane			1612 N Lak	1612 N Lakeside Dr, Andover, KS 67002				
City:	Wichita		State: KS	ZIP: 67206						
3 LOCAT		4 DEPTH		IPLETED WELL:	108' e	5 Letitud	•		(desimal degrees)	
WITH "				Encountered: 1)						
SECTION BOX: Deputits) Groundwater Encountered: 1)										
WELL'S STATIC WATER LEVEL:							or Latitude/Longitude		,,, = 1	
			below land surface, measured on (mo-day-yr)			□GPS	(unit make/model:)	
			above land surface, measured on (mo-day-yr p test data: Well water was ft.				(WAAS enabled? □		0)	
							☐ Land Survey ☐ Topographic Map			
W afterhours pu				vater was						
				s pumping	gnm					
Estimated Vield			/ield·	onm			6 Elevation:ft. Ground Level TOC			
S Bore Hole Diameter:			.10" in to 108	108' ft. and Source: Land Survey GPS Topo Other						
1 r				in. to	ft.		Utner			
7 WELL WATER TO BE USED AS: 1. Domestic: 5. \[Public Water Supply: well ID										
1. Domestic	1. Domestic: 5. ☐ Public Water Supply: w ☐ Household 6. ☐ Dewatering: how many									
	Lawn & Garden 7. ☐ Aquifer Recharge:									
1 —	Livestock 8. Monitoring: well ID									
2. Irrigati	2. ☐ Irrigation 9. Environmental Remediation: well ID									
					Extraction	traction b) Open Loop Surface Discharge Inj. of Water				
4. Industr			Recovery				r (specify):			
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:										
Water well disinfected? ☐ Yes ■ No										
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded										
Casing diameter										
Casing neight above land surface										
TYPE OF SCREEN OR PERFORATION MATERIAL: □ Steel □ Stainless Steel □ Fiberglass ■ PVC □ Other (Specify)										
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous Slot ■ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)										
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)										
SCREEN-PERFORATED INTERVALS: From										
GRAVEL PACK INTERVALS: From										
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other										
Grout Intervals: From										
Nearest source of possible contamination: Septic Tank										
Sewer			Cess Pool	Sewage L		Fuel Storage		oned Water V	Well	
■ Watertight Sewer Lines										
☐ Other (Specify)										
10 FROM	TO		ITHOLOG	GIC LOG	FROM	TO L	ITHO. LOG (cont.) or	r PLUGGINO	3 INTERVALS	
0'	3'	Top Soil								
3'	12'	Clay								
12'	75'	Brown Shale								
75	100'	Gray Shale								
85'	108'	Shaley Lime								
					Notes:					
					140tes:					
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged										
under my jurisdiction and was completed on (mo-day-year) .1.1/30/2017 and this record is true to the best of my knowledge and belief.										
Kansas Wa	iter Well Co	ontractor's Lic	ense No. 4	193 This W	ater Well Rec	ord was/comp	leted on (mo-day y	ear) .9/1.3/1	l 8	
under the b	usiness nan	ne of Reiser	er Well Dr	iiling	Si	gnature//.	Flu (1)E	15CA41.1.		
Mail I white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,										
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.										
Visit us at htt	Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015									