

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <i>Butler</i>	<i>NE 1/4 NE 1/4 NW 1/4</i>	<i>7</i>	T <i>27</i> S	R <i>3</i> <i>EW</i>

Distance and direction from nearest town or city street address of well if located within city?	
1 Mile West of Andover	
2 WATER WELL OWNER: Climateck-Heating & Cooling Kan 67210	
RR#, St. Address, Box #	Board of Agriculture, Division of Water Resources
City, State, ZIP Code	Application Number:
3445 S. Glendal Wichita	

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

4) DEPTH OF COMPLETED WELL: 105 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 90 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 30 gpm; Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 1/2 in. to ft. and in. to ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	7 Air conditioning
2 Irrigation	4 Industrial	6 Oil field water supply	8 Dewatering
		7 Lawn and garden only	10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes.....No X.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:		3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input checked="" type="checkbox"/>	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded	
2 PVC	4 ABS	7 Fiberglass		Threaded	
Blank casing diameter in. to 60		ft., Dia in. to ft., Dia		in. to ft.	
Casing height above land surface in., weight 200		lbs./ft. Wall thickness or gauge No. 1214			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement	
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)	
			9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes		
		7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS:					
From 60	ft. to 105	ft., From	ft. to	ft.	
From	ft. to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS:					
From	ft. to	ft., From	ft. to	ft.	
From	ft. to	ft., From	ft. to	ft.	

6 GROUT MATERIAL: 3 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 13 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Direction from well? W 13 Insecticide storage
How many feet? 90

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/7/86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 254 This Water Well Record was completed on (mo/day/yr) 5/13/86 under the business name of Winter Well Drilling by (signature) Charles Sinter

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.