		WATER W	ELL RECORD	For	n WW	/C-5 K	SA 82a-12	12		
1 LOCATION OF WATER	R WELL:	FRACTION			SECT	ION NUMBER	R TOWNSH	IP NUMBER	RANGE N	UMBER
Butler		NE 1/4	NE 1/4	SW 1/	4	7	T 2	27 s	R 31	E/W
Distance and direction from		street address of we	Il if located within city?							
1432 N. Shad			dover, Kansas							
2 WATER WELL O	WNER: SHA	RP HOMES								
RR#,ST. ADDRESS,	BOX #: 2131	N. Collective	e Ste #A					Board of Agri	culture, Division of V	Vater Resource
CITY, 8	STATE: Wick	hita, Kansas			ZIF	CODE: 6	7206	Application Num	ber:	
3 LOCATE WELL'S LO	CATION 4	DEPTH OF COMP	PLETED WELL:	120	ft.		ELEVATION:			
WITH AN "X" IN SEC		pth of groundwate	r Encountered:		ft.			ft.		ft.
		ELL'S STATIC WA	_	0 гт		W I AND SI	IREACE MEAS	URED ON mo/d	lay/yr: 9/11	/19
- NW	- NE			ell water w		W LAND OC	ft. after		of pumping @	gpm
1 1	~~	Est. Yield:	•	ell water v			ft. after		of pumping @	gpm
w Wile	E B	Bore Hole Diamete	4 -	on water :	to 1	20 ft.		in.	to	ft.
- -	l w	ELL WATER TO E	BE USED AS:					9. Dewateri		ction well
sw	-SE 1	1. Domestic 3.	Feedlot 5. Pub	lic water s	supply (7. Lawn a	nd garden on		'y	pecify below)
		2. Irrigation 4.	. Industrial 6. Oil 1	ield water	supply	8. Air cor	ditioning	10. Monitorin		,
S			eriological sample submit	ted to Depa	rtment?	YES	NO		vhat mo/day/yr v	-
		ubmitted				Was V	Vater Well Disir	fected?	YES I	NO
5 TYPE OF CAS		5. Wrought	t Iron 7. Fibe	rglass	9. Ot	her (Specify	below) CA	SING JOINTS: (Glued	Threaded
1. Steel	3. RPM (SI		a Compant 9 Con	crete tile	SDF	R-26			Welded	Clamped
2. PVC	> 4. ABS	6. Asbesto								
Blank casing diamete	r 5	in. to	40 ft., Di	a.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above	land surface:	12 in.,	Weigh	nt: 2. 3	5 lb	s. / ft.	Wall t	nickness or gaug	je No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3.	. Stainless Steel	Fiberglass	7. PVC	>	9. A	3S	11. O	ther (specify)		
2. Brass 4.	Galvanized	Concrete 1	Tile 8. RMP	(SR)	10. As	sbestos-Cer	nent 12. N	one used (open	hole)	
SCREEN OR PERFO	RATION OPENING	GS ARE:								
1. Continuous slot	3. Mill sl	lot 5.	Gauzed wrapped		7. Tor	ch cut	9. Dri i	led holes	11. None (c	pen hole)
2. Louvered shutter	r 4. Key p	unched 6	Wire wrapped		8. Sa v	w cut	10 00	er (specify)		
		difference o.		`	_	N COL	70. 011	iei (specily)		
SCREEN - PERFORA	TION INTERVAL	From	40 ft.	to	120	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PAG	CK INTERVALS:	From	24 ft.	to	120	ft.,	From	ft.	to	ft.
i		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIA	ALS: 1 Nact		2.6			-				
Grout letopole: 5 2. Cement Grout 3. Bentonite									-	
What is the nearest so		ontamination:	, .		ft.	to	ft.,	From	ft. to	ft.
							15. Oil well/G	as well		
2. Sewer lines	5. Cess I	Pool 8	S. Sewage lagoon	11. F	uel stor	age	14. Aband	ion water well	16. Other (sp	ecify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage										
Direction from well?	West	igo pit	,,,,,,				How m	any feet? 80 f	t, plus	
From To		LITHOLOGIC	CLOG	F	rom	То		LITHOLO		
0 3	topsoil							LIIIIOLO	CIO EGG	
	clay									
1	brown shale									
61 120	gray shale									
								· · · · · · · · · · · · · · · · · · ·		
										
								7414		
								The same of the sa		
		· · · · · · · · · · · · · · · · · · ·								
7 Contractor's or L	andawa at a min	lastics. Thi						mlumers d	and a result of all t	ion as d
0/11/10										
was completed on ((mo/day/year)	9/11/19	and this r	ecord is tru	ue to the	best of my	knowledge and	belief.		
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/13/19										
under the business name of Harn Well and Pump Service by (signature)										
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp										