


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction County: <i>Battler</i>	SE $\frac{1}{4}$ NW $\frac{1}{4}$ SE $\frac{1}{4}$	Section Number Distance and direction from nearest town or city street address of well if located within city?	Township Number <i>3 Mile West 3 Mile North of Augusta</i>	Range Number R 3 E	
2 WATER WELL OWNER:		Dale Foss		69019 Board of Agriculture, Division of Water Resources Application Number:			
RR#, St. Address, Box #:		P 3 Box K 106 Augusta					
City, State, ZIP Code:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL 105 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 85 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 30 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 85 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/>			
5 TYPE OF BLANK CASING USED:		1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded	
		2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)		
				7 Fiberglass			
Blank casing diameter		5	in. to 60	ft., Dia	.in. to ft., Dia	.in. to ft.	
Casing height above land surface		18	in. weight	200	lbs./ft. Wall thickness or gauge No.	214	
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement	
		2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)	
				5 Gauzed wrapped	9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot	3 Mill slot	6 Wire wrapped	8 Saw cut	11 None (open hole)	
		2 Louvered shutter	4 Key punched	7 Torch cut	9 Drilled holes		
SCREEN-PERFORATED INTERVALS:		From 60	ft. to 105	ft., From ft. to ft.	10 Other (specify)		
		From	ft. to ft.	From ft. to ft.			
GRAVEL PACK INTERVALS:		From	ft. to ft.	From ft. to ft.			
		From	ft. to ft.	From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other		
Grout Intervals:		From 0	ft. to 12	ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination:		1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
		2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
		3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
Direction from well?		5		How many feet? 155			
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0	3	Soil					
3	16	Clay					
16	30	Shale					
30	105	Shale & Lime					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:		This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/17/89 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 1251		This Water Well Record was completed on (mo/day/year) 3/28/89 by (signature) Charles Winter					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.							