


Copy - HP

1 LOCATION OF WATER WELL:		Fraction County: BUTLER NW $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 14	Township Number T 27 S	Range Number R 3 E E/		
Distance and direction from nearest town or city street address of well if located within city? 1 E. of Augusta Airport (Camp Towakone Rd.) go 1 3/4 N. of 54 Highway on W. side of Rd., August Ks.							
2 WATER WELL OWNER:		Neil Wilscam					
RR#, St. Address, Box #:		R.R. #1, Box 184A					
City, State, ZIP Code:		Augusta, Ks.					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:							
4 DEPTH OF COMPLETED WELL:		145 ft. ELEVATION:					
Depth(s) Groundwater Encountered:		1. 60 ft. 2. ft. 3.					
WELL'S STATIC WATER LEVEL:		60 ft. below land surface measured on mo/day/yr 11-19-81					
Pump test data: Well water was		ft. after hours pumping					
Est. Yield gpm: Well water was		ft. after hours pumping					
Bore Hole Diameter 11 in. to		ft., and in. to					
WELL WATER TO BE USED AS:		5 Public water supply	8 Air conditioning	11 Injection well			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)		
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Observation well			
Was a chemical/bacteriological sample submitted to Department? Yes		No X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes		X No					
5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . X . Clamped .			
1 Steel		3 RMP (SR)	6 Asbestos-Cement	Welded .			
2 PVC		4 ABS	7 Fiberglass	Threaded .			
Blank casing diameter 5 in. to 60 ft., Dia		in. to ft. Dia in. to					
Casing height above land surface 12 in., weight 1.59 lbs./ft.		Cer-Mac Styrene SDR-26 in. to					
Casing thickness or gauge No. .203							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement				
1 Steel		3 Stainless steel	5 Fiberglass	11 Other (specify) .			
2 Brass		4 Galvanized steel	6 Concrete tile	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut .06	11 None (open hole)			
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes			
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify) .			
SCREEN-PERFORATED INTERVALS:		From 60 ft. to 145 ft.	From ft. to ft.	ft. to ft.			
GRAVEL PACK INTERVALS:		From 14 ft. to 145 ft.	From ft. to ft.	ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other .		
Grout Intervals:		From 4 ft. to 14 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.		
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well					
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage			
Direction from well? Southeast		How many feet? 55					
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0	3	Topsoil					
3	6	Yellow Shale (Rock)					
6	90	Yellow Shale					
90	145	Gray Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and completed on (mo/day/year) 11-19-81 and this record is true to the best of my knowledge and belief. K. A. Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 1-4-82 under the business name of Harp Well & Pump Serv., Inc. by (signature) M. Arnold							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							