

## WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction County: BUTLER Distance and direction from nearest town or city street address of well if located within city?	Section Number NE $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$ 14 1 E. of Augusta Airport (Camp Towakoni Rd.), go 1 3/4 N. of 54 Hwy., on W. side of Rd.,	Township Number T 27 S Range Number R 3 E E/W		
2 WATER WELL OWNER:		Robin Siefkin Augusta, Ks. RR#, St. Address, Box # : R.R. #1, Box 189 City, State, ZIP Code : Augusta, Ks.				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 130 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 93 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 93 ft. below land surface measured on mo/day/yr 6/12/81 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No				
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 3 RMP (SR) 2 PVC 4 ABS	8 Concrete tile 6 Asbestos-Cement 7 Fiberglass	CASING JOINTS: Glued X Clamped Welded Threaded		
Blank casing diameter		5 in. to 95 ft.	9 in. to ft. Dia in. to ft.	Dia in. to ft.		
Casing height above land surface		12 in. weight 1.59 lbs./ft.	1.59 lbs./ft.	Wall thickness or gauge No. 203		
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 5 Fiberglass 6 Concrete tile	10 Asbestos-cement 8 RMP (SR) 9 ABS	11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut .06 9 Drilled holes 10 Other (specify)	11 None (open hole)		
SCREEN-PERFORATED INTERVALS:		From 95 ft. to 130 ft.	From ft. to ft.	ft. to ft.		
GRAVEL PACK INTERVALS:		From 14 ft. to 130 ft.	From ft. to ft.	ft. to ft.		
6 GROUT MATERIAL:		1 Neat cement Grout Intervals: From 40" ft. to 14 ft.	2 Cement grout	3 Bentonite 4 Other		
What is the nearest source of possible contamination:		1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well? Northwest		How many feet? 75				
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	
0	2	Topsoil				
2	19	Clay				
19	76	Blue Shale				
76	80	Red Shale				
80	130	Blue Shale				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:		This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/12/81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 8-7-81 under the business name of Harp Well & Pump Serv., Inc. by (signature) <i>Arnold</i>				
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.						