


1 LOCATION OF WATER WELL:	Fraction County: Butler	NE $\frac{1}{4}$ NW $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 14	Township Number T 27 S	Range Number R 3 EW
Distance and direction from nearest town or city street address of well if located within city? 5 West 2 N of Augusta					

2 WATER WELL OWNER:	Duane Creek More Andover KS 67002				
RR#, St. Address, Box #	Board of Agriculture, Division of Water Resources				
City, State, ZIP Code	Application Number:				

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 105 ft. ELEVATION: 105
--	---

 1 Mile	Depth(s) Groundwater Encountered 1. 75 ft.	ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 20 ft below land surface measured on mo/day/year	9-12-83
Pump test data: Well water was Est. Yield 35 gpm Well water was Bore Hole Diameter 8 in. to 105 ft. and	ft. after hours pumping gpm	
	ft. after hours pumping gpm	
WELL WATER TO BE USED AS: ① Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below)	ft. in. to ft.	
	Was a chemical/bacteriological sample submitted to Department? Yes No. X If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes X No		

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped .
1 Steel	③ RMP (SR)	6 Asbestos-Cement	Welded .
2 PVC	4 ABS	7 Fiberglass	Threaded.

Blank casing diameter 5 in. to 105.50 ft. Dia. in. to ft. Dia. in. to ft.

Casing height above land surface 15 in., weight 2.00 lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement
1 Steel	③ RMP (SR)	11 Other (specify) .
2 Brass	6 Fiberglass	12 None used (open hole)
3 Stainless steel	5 Concrete tile	8 Saw cut 11 None (open hole)
4 Galvanized steel	9 Gauzed wrapped	9 Drilled holes
4 Key punched	6 Wire wrapped	10 Other (specify) .

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	10 Asbestos-cement
2 Louvered shutter	4 Key punched	6 Wire wrapped	11 Other (specify) .
5 Louvered slot	7 Torch cut	7 PVC	12 None used (open hole)

SCREEN-PERFORATED INTERVALS: From. 50 ft. to 105 ft. From. ft. to ft. From. ft. to ft.

GRAVEL PACK INTERVALS: From. 40 ft. to 105 ft. From. ft. to ft. From. ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 40-147

Grout Intervals: From. 3 ft. to 14 ft. From. ft. to ft. From. ft. to ft. From. ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	⑧ Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)

Direction from well? S E How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	SOIL			
2	18	ROCK			
18	30	CLAY			
30	50	SHALE			
50	85	LIME			
85	105	SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-12-83 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 251 This Water Well Record was completed on (mo/day/year) 12-27-83 under the business name of Winter Well Drill by (signature) Charles Winter

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.