WATER WELL R	ECORD Fo	orm WWC-5		sion of Water				
Original Record	Correction	Change in Well Use	Reso	urces App. No.		Well ID		
1 LOCATION OF W					ge Number			
County: Butler		NE 1/4 NE 1/4 SW						
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and								
Business: Richard Moeder Custom Homes direction from nearest town or intersection): If at owner's address, check here:							heck here: 🔲 📗	
Address: 4700 W. Irving Address: 922 Ledgestone St, Andover, KS 67002								
	State	: KS ZIP: 67209	ozz zoagoo.		,			
3 LOCATE WELL								
WITH "X" IN		COMPLETED WELL			<b>:</b> :			
SECTION BOX:		Depth(s) Groundwater Encountered: 1)ft. Longitude:						
N		ft. 3) ft., or 4			al Datum: WGS 8		33 □ NAD 27	
	WELL'S STATIC WATER LEVEL:							
	□ below land surface, measured on (mo-day-yr)       □ GPS (unit make/model:							
NW NE		Pump test data: Well water was						
W E		afterhours pumpinggpm Daline Mapper:						
	1	Well water was ft.						
SW SE	after hours pumping							
	Estimated Yield:							
S								
7 WELL WATER TO BE USED AS: 1. Domestic: 5. □ Public Water Supply: well ID								
1. Domestic:		lic Water Supply: well ID		10. UU OH F	ieid water supply: I	ease	****************	
☐ Household ☐ Lawn & Garden		vatering: how many wells? nifer Recharge: well ID		11. Test Hole: well ID				
Livestock		nitoring: well ID		12. Geothermal: how many bores?				
2. Irrigation		nmental Remediation: wel		a) Closed Loop				
3. Feedlot		Sparge Soil Vape		b) Open Loop  Surface Discharge  Inj. of Water				
4. Industrial	☐ Rec	covery		13. 🔲 Other	r (specify):			
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No If yes, date sample was submitted:								
Water well disinfected?								
8 TYPE OF CASING	USED: ☐ Steel	■ PVC □ Other	CASIN	IG JOINTS:	Glued Clampe	d   Welded	Threaded	
Casing diameter 5" in to 106 ft. Diameter in to ft. Diameter in to ft.								
Casing diameter 5" in to 106 ft., Diameter in to ft. Diameter in to ft. Casing height above land surface 12" in Weight 160 lbs./ft. Wall thickness or gauge No								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)								
Louvered Shutter    Key Punched    Wire Wrapped    Saw Cut    None (Open Hole)  SCREEN-PERFORATED INTERVALS: From								
GRAVEL PACK INTERVALS: From 23' ft. to 106 ft., From ft. to ft., From ft. to ft.								
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
Nearest source of possible contamination:								
Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage								
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well								
■ Watertight Sewer Lines								
Other (Specify)								
Direction from well? . VVE	est	Distance from	well?15					
10 FROM TO		OLOGIC LOG	FROM	TO LI	THO. LOG (cont.) o	r PLUGGINO	3 INTERVALS	
	dirt							
	clay						<u> </u>	
	imestone							
	gray shale							
55 106 \$	shaley lime							
			Notes:					
11 CONTRACTORS OF LANDOWNERS CERTIFICATION TO								
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo-day-year) .6/22/16								
under the business name of Reiserer Well Drilling Signature Lerry Reiserer								
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health ap Environment, Bureau of Water, GWTS Section,								
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.								
Visit us at http://www.kdheks			KSA 82a-12				7/10/2015	