			WWC-5	Divi	sion of Water			
			ge in Well Use	Reso	urces App. No.		Well ID	
1 LOCA	TION OF V	VATER WELL:	Fraction	Sec	ion Number	Township Number		
Count	y: Butler		NW 1/4 NW 1/4 SE 1/	4 1/4	6 T 27 S R 3 ■ E □ W			
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance a								
	Sharp Ho				earest town or intersection). If at owner's address, check here:			
Address:		lective Ln.						
Address:				2419 Sands	tone St, Ando	ne St, Andover, KS 67002		
City:	Wichita	State: KS	ZIP: 67206					
3 LOCAT	E WELL	4 DEPTH OF COL	MDI ETER MELL	117 a	5 7 414 1			
WITH "	'X" IN		MPLETED WELL:	The second secon				
SECTIO	ON BOX:		Encountered: 1)		Longitue	de:	(decimal degrees)	
3	N		3) ft., or 4)				I □ NAD 83 □ NAD 27	
		process and the second	ATER LEVEL:			r Latitude/Longitude:		
<u>'</u>	,		e, measured on (mo-day e, measured on (mo-day			· ·)	
NW	NE		water was			(WAAS enabled?		
w			rs pumping			☐ Land Survey ☐ Topographic Map		
W	E		water was					
			rs pumping					
Estimated Yield:			gnm		6 Elevation:ft. Ground Level TOC			
	S	Bore Hole Diameter:	10" in to 117	ft and		Source: Land Survey GPS Topographic Map		
	mile		in. to ft.			Other		
7 WELL WATER TO BE USED AS: 1. Domestic: 5. Public Water Supply: well ID								
1. Domestic					IV. UII FI	eid water Supply: Te	asc	
			ng: how many wells?		11. Test Hole: well ID			
			Recharge: well ID					
						12. Geothermal: how many bores?		
3. Feedlo				a) Closed Loop				
3. ☐ Feedlot ☐ Air Sparge 4. ☐ Industrial ☐ Recovery								
		9 8 9						
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No If yes, date sample was submitted:								
Water well disinfected? ☐ Yes ■ No								
8 TYPE OF CASING USED: ☐ Steel ☐ PVC ☐ Other CASING JOINTS: ☐ Glued ☐ Clamped ☐ Welded ☐ Threaded								
Casing diameter 5" in to 117 ft. Diameter in to ft. Diameter in to ft.								
Casing diameter 5" in to 117 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 12" in Weight 160 lbs/ft. Wall thickness or gauge No.								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous Slot								
Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)								
SCREEN-PERFORATED INTERVALS: From								
GRAVEL PACK INTERVALS: From 22' ft. to 117 ft., From ft. to ft., From ft. to ft.								
9 CPOIT MATERIAL TOWN AND TOWN								
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
Septic			□ D: D :					
Sewer		☐ Lateral Lin			Livestock Pens		ide Storage	
		Cess Pool	Sewage L		Fuel Storage		oned Water Well	
■ Watertight Sewer Lines								
☐ Other (Specify) Direction from well? .E. Distance from well? .40 ft.								
10 FROM	TO	LITUOLO	CICLOC				DI LICONO DIERRITATA	
0		LITHOLO	GIC TOR	FROM	10 LI	THU. LUG (cont.) or	PLUGGING INTERVALS	
		dirt					***************************************	
2		clay						
50		shale						
80	117	shaley lime						
		100						
				Notes:			·	
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo-day-year) .4/15/16								
Kansas Wa	iter Well Co	ntractor's License No	493 This W	ater Well Rec	and was onment	eted on (man-day-ye	ear) 11/30/19	
under the h	ousiness nam	e of Reiserer Well D	rilling	Sig	nature (rry Reiser	er	
under the business name of Reiserer Well Drilling Signature Wall Drilling Signature Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,								
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.								
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015								