

1 LOCATION OF WATER WELL:

FRACTION

Butler

NE

1/4

NW

1/4

SE

1/4

Section Number

Township Number

Range Number

18

T

27

S

R

3E

E/W

Distance and direction from nearest town or city street address of well if located within city?

847 Prosperity Lane

Andover, Kansas

2 WATER WELL OWNER: LASSMAN, Doriane

Board of Agriculture, Division of Water Resource


RR#, ST. ADDRESS, BOX #: 847 Prosperity Lane

CITY, STATE, ZIP CODE: Andover, Kansas

67002

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION:

Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 46 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 05/19/1994

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter in. to ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No  ; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes  No

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR)

5 Wrought iron

8 Concrete tile

CASING JOINTS:

Glued

Clamped

2 PVC 4 ABS

6 Asbestos-Cement

9 Other (Specify below)

Welded

Threaded 

Blank casing Diameter 6 in. to ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 36 in., weight lbs. / ft.

Wall thickness or gauge No.

10 Asbestos-cement

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel

5 Fiberglass

7 PVC

11 other (specify)

2 Brass 4 Galvanized steel

6 Concrete tile

8 RMP (SR)

12 None used (open hole)

SCREEN OR PERFORATION OPENING ARE:

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

1 Continous slot 3 Mill slot

6 Wire wrapped

9 Drilled holes

2 Louvered shutter 4 Key punched

7 Torch cut

10 Other (specify)

SCREEN-PERFORATION INTERVALS: from ft. to ft., From ft. to ft.

from ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: from ft. to ft., From ft. to ft.

from ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 2.5 ft. to 13 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandon water well

2 Sewer lines 5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well? East

How many feet? 15

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0	2.5	surface sands and silts
2.5	13	cement grout
13	46	bentonite hole plug
46	80	chlorinated sand and gravel

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/19/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 05/19/94 Under the business name of Harp Well &amp; Pump Service, Inc by (signature)

Jane Frederick