


1 LOCATION OF WATER WELL:		FRACTION <b>SW SE SE NW</b> <b>NE 1/4 NE 1/4 SW 1/4</b>	Section Number <b>19</b>	Township Number <b>T 27 S</b>	Range Number <b>R 3E E/W</b>
Distance and direction from nearest town or city street address of well if located within city? <b>1007 Walnut Andover, Kansas</b>					
2 WATER WELL OWNER: <b>ENGLERT, DON</b>		Board of Agriculture, Division of Water Resource Application Number:			
RR#, ST. ADDRESS, BOX #: <b>1007 Walnut</b>					
CITY, STATE, ZIP CODE: <b>Andover, Kansas</b>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		<b>4 DEPTH OF COMPLETED WELL 90 ft. ELEVATION:</b> Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. <b>WELL'S STATIC WATER LEVEL 21 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 02/07/1994</b> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 90 ft. and in. to ft. <b>WELL WATER TO BE USED AS:</b> 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No			
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (Specify below)	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded	
Blank casing Diameter 5 in. to 25		ft., Dia	in. to	ft., Dia	in. to ft.
Casing height above land surface 12 in.,		weight 2.35 lbs. / ft.	7 PVC	Wall thickness or gauge No. 10 Asbestos-cement .214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel  5 Fiberglass 6 Concrete tile  8 Gauzed wrapped 6 Wire wrapped 7 Torch cut  9 ABS  11 other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENING ARE: 1 Continous slot 3 Mill slot 2 Louvered shutter 4 Key punched  5 Gauzed wrapped 6 Wire wrapped 7 Torch cut  9 ABS  10 Other (specify)					
SCREEN-PERFORATION INTERVALS: from 25 ft. to 90 ft., From ft. to ft.  GRAVEL PACK INTERVALS: from 24 ft. to 90 ft., From ft. to ft.  ft., From ft. to ft.  ft., From ft. to ft.  ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.  What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard  10 Livestock pens 14 Abandon water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below)  Direction from well? <b>East</b> How many feet? <b>20</b>					
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	3	<b>topsoil</b>			
3	11	<b>clay</b>			
11	62	<b>brown shale</b>			
62	90	<b>grey shale</b>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <b>02/07/1994</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>236</b> This Water Well Record was completed on (mo/day/yr) <b>02/09/94</b> . Under the business name of <b>Harp Well &amp; Pump Service, Inc.</b> by (signature) <b>Jane Frederick</b>					