


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction SW 1/4 SW 1/4 SW 1/4	Section Number 19	Township Number T 27 S	Range Number R 3 E E/W
Distance and direction from nearest town or city street address of well if located within city? 16048 E. Central, Wichita, Ks.					
2 WATER WELL OWNER:		Tom Fylnn		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box # :		16048 E. Central		Application Number:	
City, State, ZIP Code		Wichita, Ks.			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					
		4 DEPTH OF COMPLETED WELL 95 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 82 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 3.5 ft. below land surface measured on mo/day/yr 6/26/81 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile
		2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)
Blank casing diameter		5	35	7 Fiberglass	CASING JOINTS: Glued X Clamped Welded Threaded
Casing height above land surface		12	in., weight 1.59	ft., Dia in. to ft., Dia in. to ft.	lbs./ft. Wall thickness or gauge No. Gert Mac Styrene SDR-26 203
6 TYPE OF SCREEN OR PERFORATION MATERIAL:					
SCREEN OR PERFORATION OPENINGS ARE:		1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
		2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot	3 Mill slot	5 Gauzed wrapped	10 Asbestos-cement
		2 Louvered shutter	4 Key punched	6 Wire wrapped	11 Other (specify)
SCREEN-PERFORATED INTERVALS:		From 35	ft. to 95	7 Torch cut	12 None used (open hole)
		From	ft. to	8 Saw cut 06	11 None (open hole)
GRAVEL PACK INTERVALS:		From 14	ft. to 95	9 Drilled holes	10 Other (specify)
		From	ft. to	10 Other (specify)	ft. to
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:		From 40"	ft. to 14	ft., From ft. to ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines		6 Seepage pit		13 Insecticide storage	
Direction from well?		West			
FROM		TO		LITHOLOGIC LOG	
0	3	Topsoil		FROM	TO
3	5	Clay			
5	71	Brown Shale			
71	95	Grey Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/26/81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 8-7-81 under the business name of Harp Well & Pump Serv., Inc. by (signature) m. Arnold					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					