


1 LOCATION OF WATER WELL:		Fraction SW 1/4 NE 1/4 NE 1/4	Section Number 19	Township Number T 27 S	Range Number R 3E E		
Distance and direction from nearest town or city street address of well if located within city? 313 Lioba Andover, Kansas							
2 WATER WELL OWNER:		Snyder, Jerry					
RR#, St. Address, Box #:		313 Lioba					
City, State, ZIP Code:		Andover, Kansas					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:							
4 DEPTH OF COMPLETED WELL:		.90 ft. ELEVATION: .30 ft.					
Depth(s) Groundwater Encountered:		1 ft. 2 ft. ft. 3 ft.					
WELL'S STATIC WATER LEVEL:		.30 ft. below land surface measured on mo/day/yr					
Pump test data: Well water was		ft. after hours pumping gpm					
Est. Yield gpm: Well water was		ft. after hours pumping gpm					
Bore Hole Diameter in. to		ft. and in. to ft.					
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 <u>Lawn and garden</u> only 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes		No XX ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes		XX No					
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued XX Clamped					
1 Steel <u>3 RMP (SR)</u>		8 Concrete tile Welded					
2 PVC <u>4 ABS</u>		9 Other (specify below) Cer-Mac styrene SDR-26 Threaded					
Blank casing diameter in. to .30 ft., Dia.		in. to ft., Dia. in. to ft.					
Casing height above land surface .12 in., weight 1.59		lbs./ft. Wall thickness or gauge No. .203					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement					
1 Steel 3 Stainless steel		5 Fiberglass <u>8 RMP (SR)</u> 11 Other (specify)					
2 Brass 4 Galvanized steel		6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot		6 Wire wrapped 5 Drilled holes					
2 Louvered shutter 4 Key punched		7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From .30 ft. to .90 ft.		ft. to ft. From .ft. to ft.					
From .ft. to .ft.		ft. to ft. From .ft. to ft.					
GRAVEL PACK INTERVALS: From .14 ft. to .90 ft.		ft. to ft. From .ft. to ft.					
From .ft. to .ft.		ft. to ft. From .ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement		2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From .4 ft. to .14 ft.		ft. to ft., From .ft. to ft., From .ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well					
1 Septic tank 4 Lateral lines		11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool		12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit		13 Insecticide storage					
Direction from well? <u>South</u>		How many feet? <u>16</u>					
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0	3	Topsoil					
3	12	Clay					
12	65	Brown Shale					
65	70	Gray Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) <u>reconstructed</u> , or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) <u>8-28-85</u> and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's License No. <u>236</u> This Water Well Record was completed on (mo/day/yr) <u>12-9-85</u>							
under the business name of <u>Harp Well & Pump Service, Inc.</u> by (signature) <u>Mary Orneid</u>							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							