WATE	R WELL RECORD F	orm WV	VC-5 K	SA 82a-121	2		
1 LOCATION OF WATER WELL: FRACTIO		SEC	TION NUMBE	R TOWNSH	P NUMBER	RANGE NUM	BER
Butler NW	1/4 NW 1/4 NE	1/4	5	т 2	7 s	R 3E	E/W
Distance and direction from nearest town or city street addres	•						•
1008 E. Flint Hills National Parkwa		Andove	er, Kansa	ıs			
	TERPRISES				Roard of Agri	culture, Division of Wat	er Resource
	b Road, Suite #100			7306	board of Agri	Collaid, Division of vega	oi Noscarco
CITY, STATE: Wichita, Kar			IP CODE:	7/200	Application Num	nber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF	PONSES CONNELL: 35		;	ELEVATION:			
	ndwater Encountered: No	Water n			ft.		, ft.
WELL'S STA	TIC WATER LEVEL	FT. BELO	W LAND S	URFACE MEASI	JRED ON mo/d	lay/yr: 11/3/2	20
NWNE	Pump test data: Well wat	ter was		ft. after	hours	of pumping @	gpm
<u>o</u> Est. Yield	i: gpm Well wat	ter was		ft. after	hours	of pumping @	gpm
Est. Yield	iameter ' in.	to	f	and	in.	to	ft.
	R 1045 USED AS:				9. Dewateri	ng 11. Injecti	on well
1. Domestic	_	ter supply		and garden only		12. Other (Spe	cify below)
2. Irrigation			'	nditioning	10. Monitorir	•	
S Was a chemic submitted	al/bacteriological sample submitted to D	Department?	YES	NO No Water Well Disin		what mo/day/yr was	
5 TYPE OF CASING USED:		 					
1. Steel 3. RPM (SR) 5. W	frought Iron 7. Fiberglass	9. O	ther (Specif	y below) CAS	SING JOINTS:		hreaded
(-14	sbestos-Cement 8. Concrete til	le styr	rene			Welded (Clamped
Blank casing diameter open hole in.	to ft., Dia.	in.	to	ft.,	Dia.	:a 4a	
oppu note				,		in. to	ft.
	in., Weight:	I	bs. / ft.	Wall th	ickness or gaug	je No.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)							
The state of the s							
	crete Tile 8. RMP (SR)	10. A	sbestos-Ce	ment 12. No	one used (open	noie)	
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot 3. Mill slot	5. Gauzed wrapped	7. To	rch cut	9. Dril	led holes	11. None (ope	en hole)
2. Louvered shutter 4. Key punched	6. Wire wrapped	8. Sa	w cut	10. Oth	er (specify)		
SCREEN - PERFORATION INTERVAL From	ft. to		ft.,	From	•	4-	
From	ft. to				ft.	to .	ft.
000000000000000000000000000000000000000			ft.,	From	ft.	to	ft.
			ft.,	From	ft.	to	ft.
From	ft. to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement	2. Cement Grout	3	3. Bentonite)	Other bent	onite hole plug	
Grout Intervals: From 8 ft.	to 35 ft., From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination		0 Livestoc	k pens	13 Ineact	ioldo etomas	15. Oil well/Gas	wall
At Charles							
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)							
3. Watertight sewer line 6. Seepage pit	9. Feed yard 1	2. Fertilize	r storage				
Direction from well? From To LITHOL	0010100	T =		How ma	any feet?		
From To LITHOL	OGIC LOG	From	To			GIC LOG	
		0	8	compacted			
		8	35	bentonite h	ole plug		·
			······································			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
7							
Contractor's or Landowner's Certification: This		2. re c	constructe	or 3.	plugged	ınder my jurisdiction	and
was completed on (mo/day/year) 11/3/20 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/5/2020							
under the business name of Harp Well and			nature)				
I maip wen and	i a amp sei vice	Oy (31)		1 (TUUV S.	.Harb	