WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER	1	RANGE NUMBER
Butler SW 1/4 NE 1/4 SW	1/4 8	T 27 S	R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? O E.Watercress St., Reserve A Andover, Kansas 67	002		
2 WATER WELL OWNER: KELSEY DEVELOPMENT INC,			
RR#,ST. ADDRESS,BOX #: 716 N. 119th St. W. Ste #120		Board of Agr	iculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE: 6	7235 Application Nur	mber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 8		ELEVATION:	
WITH AN "X" IN SECTION BOX: N Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 26	FT. BELOW LAND SU	JRFACE MEASURED ON mo/	day/yr: 1/5/21
Pump test data: Well wa	ter was	ft. after hours	s of pumping @ gpm
	ter was	ft. after hour	s of pumping @ gpm
	to 86 ft.	. and in.	to ft.
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public wa	iter supply 7. Lawn	9. Dewater	•
		nditioning 10. Monitori	12. Other (Specify below) ng well
S Was a chemical/bacteriological sample submitted to	Department? YES	NO ; If yes,	what mo/day/yr was sample
submitted	Was \	Water Well Disinfected?	YES NO
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR)	9. Other (Specify	below) CASING JOINTS:	Glued Threaded
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete	tile SDR-26		Welded Clamped
Blank casing diameter 5 in. to 40 ft., Dia.	in. to	ft., Dia.	in. to ft.
10		,	
Casing height above land surface: 12 in., Weight: TYPE OF SCREEN OR PERFORATION MATERIAL:	2.35 lbs. / ft.	Wall thickness or gau	ge No214
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Ce	ment 12. None used (oper	hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
40	86 ft.	_	
	,	From ft.	to ft.
From ft. to GRAVEL PACK INTERVALS: From 24 ft. tt	,	From ft.	to ft.
, , , , , , , , , , , , , , , , , , ,	,	From ft.	to ft.
- L OPOUT MATERIALO	o ft.,	From ft.	to ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite		tonite hole plug
Grout Intervals: From ft. to ft., From What is the nearest source of possible contamination:	ft. to	ft., From 4	ft. to 24 ft.
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage			
Direction from well? South		How many feet? 120	
From To LITHOLOGIC LOG	From To	LITHOLO	OGIC LOG
0 3 topsoil 3 10 clay			
10 45 brown shale	 		
45 80 gray shale			
80 86 limestone			
	+		——————————————————————————————————————
7 Contractor's or Landowner's Certification: This water well was 4	d) 0 manataurt	d or 2 physical	under my jurisdiction and
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 1/8/2021 and this record is true to the best of my knowledge and belief			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 1/5/2021			
under the business name of Harp Well and Pump Service	by (signature)	Todd S	S. Harp