

1 LOCATION OF WATER WELL:		Fraction County: Butler	NE $\frac{1}{4}$	NW $\frac{1}{4}$	SW $\frac{1}{4}$	Section Number 23	Township Number 27	Range Number R 3 EW
Distance and direction from nearest town or city street address of well if located within city? 3 mi. EAST AND 1/2 MI. NORTH of Andover AT US 54								
2 WATER WELL OWNER:		Quincy Poore						
RR#, St. Address, Box #:		RR# 3						
City, State, ZIP Code:		Augusta, Ks. 67010						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION: ft. Depth(s) Groundwater Encountered 1. 80 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 29 ft. below land surface measured on mo/day/yr 5/22/92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 50 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No						
5 TYPE OF BLANK CASING USED:		1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped Welded Threaded		
		2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)			
				7 Fiberglass				
Blank casing diameter		5		in. to ft., Dia in. to ft., Dia in. to ft.				
Casing height above land surface		12		in., weight 160 lbs./ft. Wall thickness or gauge No.				
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel		3 Stainless steel		5 Fiberglass	8 RMP (SR)	10 Asbestos-cement		
2 Brass		4 Galvanized steel		6 Concrete tile	9 ABS	11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot		3 Mill slot		5 Gauzed wrapped	8 Saw cut	11 None (open hole)		
2 Louvered shutter		4 Key punched		6 Wire wrapped	9 Drilled holes			
				7 Torch cut	10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 40 ft. to 110 ft., From ft. to ft. From ft. to ft. From ft. to ft.								
GRAVEL PACK INTERVALS: From 20 ft. to 110 ft., From ft. to ft. From ft. to ft. From ft. to ft.								
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other			
Grout Intervals:		From 3 ft. to 20 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.			
What is the nearest source of possible contamination:								
1 Septic tank		4 Lateral lines		7 Pit privy	10 Livestock pens	14 Abandoned water well		
2 Sewer lines		5 Cess pool		8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well		
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	12 Fertilizer storage	16 Other (specify below)		
13 Insecticide storage								
Direction from well? <i>down slope</i> How many feet? 50 ft								
FROM	TO	LITHOLOGIC LOG			FROM	TO	PLUGGING INTERVALS	
0	5	dirt						
5	16	brown clay						
16	60	yellow clay						
60	64	" " & broken rock						
64	80	red bed						
80	110	lime (grey)						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/22/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) under the business name of <i>Russell Well Drilling</i> by (signature) <i>Deeby Russell</i>								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								